

30-039-25589

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Burlington Resources Location: Unit H Sec 28 Twp 28 Rng 5

Name of Well/Wells or Pipeline Serviced San Juan 28-5 #64M

Elevation _____ Completion Date 2-1997 Total Depth 120' Land Type _____

Casing Strings, Sizes, Types & Depths 20' 8" PUC casing

If Casing Strings are cemented, show amounts & types used yes-4 Bags

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 70', 90' + 100' Fresh

Depths gas encountered: None

Ground bed depth with type & amount of coke breeze used: 120' 1000/lbs
SW Coke Breeze

Depths anodes placed: 1-115', 96, 90, 84, 75

Depths vent pipes placed: Surface to 120'

Vent pipe perforations: Bottom to 100'

Remarks: _____

RECEIVED
FEB 25 1998

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Contractors of Cathodic Protection Services

CPE GROUND BED CONSTRUCTION WORKSHEET

ENTER

REMARKS (notes for construction log)
 Drill 11" hole 20' and set 20' of 8" casing and cement (4 Bags cement)
 Drill 8" hole from 20' - 120' and set 5 anodes and 1000 lbs coke breeze
 Water at 70', 90', + 100' (120' Vent pipe)