

3260

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFI

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 599-3400

RECEIVED
FEB 10 1998
OIL CON. DIV.
DIST. 3

30-039-25658

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 30-5 #110-M

ADDITIONAL WELLS: N/A

LEGAL LOCATION E-16-30-5

DATE OF INSTALLATION: 7/1/97

LEASE NUMBER: E-347-41

TYPE OF LEASE: STATE

PPCO RECTIFIER NUMBER: FM-603

TOTAL G/B DEPT 340

GROUND BED INFORMATION

CASING SIZE: 8

CASING TYPE: PVC

CASING DEPTH: 20

CASING CEMENT: YES

TOP ANODE: 205

BOTTOM ANODE 325

INDIVIDUAL ANODE DEPTHS 205,215,230,240,250,260,290,300,315,325

AMOUNT OF COKE: 2300

WATER INFORMATION

WATER DEPTH (1): 120

WATER DEPTH (2): NA

CEMENT PLUGS: NA

OTHER INFORMATION

GAS DEPTH: NA

VENT PIPE DEPTH 340

TOP OF VENT PERFORATIONS: 200

REMARKS: NEW G/B DRILLED 7-97

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

PPCO.GROUNDBED LOG

PHILLIPS PETROLEUM CO.			DEEP WELL CATHODIC PROTECTION GROUNDBED LOG—DATA SHEET																																																																																																																																																																							
DRILLED BY: (DRILLER'S NAME AND COMPANY) <i>Jack Ledbetter - Terra Dynamic</i>																																																																																																																																																																										
LOCATION NAME: <i>SS 30-5 #110 M</i>			DATE DRILLED: <i>7-1-97</i>																																																																																																																																																																							
LEGAL LOCATION: <i>E-16-30-5</i>			SIZE AND TYPE OF CASING: <i>8" PVC</i>																																																																																																																																																																							
PPCO ID NO. (FM NO.) <i>603</i>			DEPTH OF CASING: <i>20'</i>																																																																																																																																																																							
TOTAL DEPTH: <i>340'</i>			COKE: (CIRCLE) <i>PETR.</i> OR MET. AMOUNT: <i>2300</i> LBS.																																																																																																																																																																							
DIAMETER OF HOLE: <i>6 3/4</i>			TYPE OF ANODES: <i>Anotec</i>																																																																																																																																																																							
COUNTY: <i>Rio Arriba</i>																																																																																																																																																																										
COMPLETION INFORMATION:																																																																																																																																																																										
DEPTH FT.	LOG	ANODE	DEPTH FT.	LOG	ANODE																																																																																																																																																																					
100	.9		265	.9																																																																																																																																																																						
105	.9		270	.7																																																																																																																																																																						
110	.9		275	.6																																																																																																																																																																						
115	1.0		280	.8																																																																																																																																																																						
120	1.3	H ₂ O	285	.9																																																																																																																																																																						
125	1.1		290	1.1	4																																																																																																																																																																					
130	1.0		295	1.2																																																																																																																																																																						
135	1.2		300	1.0	3																																																																																																																																																																					
140	1.1		305	.9																																																																																																																																																																						
145	1.0		310	.9																																																																																																																																																																						
150	1.0		315	1.1	2																																																																																																																																																																					
155	1.2		320	.9																																																																																																																																																																						
160	.9		325	.8	1																																																																																																																																																																					
165	.8		330	.8																																																																																																																																																																						
170	.9		335	T.D.																																																																																																																																																																						
175	.8		340																																																																																																																																																																							
180	.8		345																																																																																																																																																																							
185	.9		350																																																																																																																																																																							
190	.9		355																																																																																																																																																																							
195	.9		360																																																																																																																																																																							
200	.8		365																																																																																																																																																																							
205	1.1	10	370																																																																																																																																																																							
210	1.0		375																																																																																																																																																																							
215	1.1	9	380																																																																																																																																																																							
220	.9		385																																																																																																																																																																							
225	1.1		390																																																																																																																																																																							
230	1.2	8	395																																																																																																																																																																							
235	1.2		400																																																																																																																																																																							
240	1.0	7	405																																																																																																																																																																							
245	1.0		410																																																																																																																																																																							
250	1.1	6	415																																																																																																																																																																							
255	1.3		420																																																																																																																																																																							
260	1.0	5	425																																																																																																																																																																							
<table border="1"> <thead> <tr> <th>WATER DEPTH</th> <th>VENT PIPE PERFS</th> <th>ISOLA- TION PLUGS</th> <th>OUTPUT NO COKE</th> <th>OUTPUT COKED</th> </tr> </thead> <tbody> <tr> <td>1) 120'</td> <td>TOP:</td> <td>1)</td> <td></td> <td></td> </tr> <tr> <td>2)</td> <td>BTM:</td> <td>2)</td> <td></td> <td></td> </tr> <tr> <td>ANODE#</td> <td>DEPTH</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1</td> <td>325</td> <td></td> <td>.9</td> <td>2.4</td> </tr> <tr> <td>2</td> <td>315</td> <td></td> <td>1.1</td> <td>2.8</td> </tr> <tr> <td>3</td> <td>300</td> <td></td> <td>1.1</td> <td>3.6</td> </tr> <tr> <td>4</td> <td>290</td> <td></td> <td>1.1</td> <td>4.0</td> </tr> <tr> <td>5</td> <td>260</td> <td></td> <td>1.2</td> <td>3.0</td> </tr> <tr> <td>6</td> <td>250</td> <td></td> <td>1.1</td> <td>4.9</td> </tr> <tr> <td>7</td> <td>240</td> <td></td> <td>1.0</td> <td>4.8</td> </tr> <tr> <td>8</td> <td>230</td> <td></td> <td>1.3</td> <td>5.2</td> </tr> <tr> <td>9</td> <td>215</td> <td></td> <td>1.2</td> <td>5.3</td> </tr> <tr> <td>10</td> <td>205</td> <td></td> <td>1.1</td> <td>4.4</td> </tr> <tr> <td>11</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>12</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>13</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>14</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>16</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>17</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>18</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>19</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>20</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>21</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>22</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>23</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>24</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>25</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>26</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>27</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>28</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>29</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						WATER DEPTH	VENT PIPE PERFS	ISOLA- TION PLUGS	OUTPUT NO COKE	OUTPUT COKED	1) 120'	TOP:	1)			2)	BTM:	2)			ANODE#	DEPTH				1	325		.9	2.4	2	315		1.1	2.8	3	300		1.1	3.6	4	290		1.1	4.0	5	260		1.2	3.0	6	250		1.1	4.9	7	240		1.0	4.8	8	230		1.3	5.2	9	215		1.2	5.3	10	205		1.1	4.4	11					12					13					14					15					16					17					18					19					20					21					22					23					24					25					26					27					28					29				
WATER DEPTH	VENT PIPE PERFS	ISOLA- TION PLUGS	OUTPUT NO COKE	OUTPUT COKED																																																																																																																																																																						
1) 120'	TOP:	1)																																																																																																																																																																								
2)	BTM:	2)																																																																																																																																																																								
ANODE#	DEPTH																																																																																																																																																																									
1	325		.9	2.4																																																																																																																																																																						
2	315		1.1	2.8																																																																																																																																																																						
3	300		1.1	3.6																																																																																																																																																																						
4	290		1.1	4.0																																																																																																																																																																						
5	260		1.2	3.0																																																																																																																																																																						
6	250		1.1	4.9																																																																																																																																																																						
7	240		1.0	4.8																																																																																																																																																																						
8	230		1.3	5.2																																																																																																																																																																						
9	215		1.2	5.3																																																																																																																																																																						
10	205		1.1	4.4																																																																																																																																																																						
11																																																																																																																																																																										
12																																																																																																																																																																										
13																																																																																																																																																																										
14																																																																																																																																																																										
15																																																																																																																																																																										
16																																																																																																																																																																										
17																																																																																																																																																																										
18																																																																																																																																																																										
19																																																																																																																																																																										
20																																																																																																																																																																										
21																																																																																																																																																																										
22																																																																																																																																																																										
23																																																																																																																																																																										
24																																																																																																																																																																										
25																																																																																																																																																																										
26																																																																																																																																																																										
27																																																																																																																																																																										
28																																																																																																																																																																										
29																																																																																																																																																																										
LOGGING VOLTS: <i>11.72</i>			VOLTAGE SOURCE: <i>Auto</i>																																																																																																																																																																							
TOTAL AMPS: <i>13.1</i>			TOTAL G/B RESISTANCE: <i>.89</i>																																																																																																																																																																							
REMARKS:																																																																																																																																																																										