

3256

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFI

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 599-3400

30-039-25677

RECEIVED
FEB 10 1998
OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 30-5 #52-M

ADDITIONAL WELLS: NA

LEGAL LOCATION I-15-30-5

DATE OF INSTALLATION: 7/2/97

LEASE NUMBER: SF-078997

TYPE OF LEASE: FEDERAL

PPCO RECTIFIER NUMBER: FM-607

TOTAL G/B DEPT 360

GROUND BED INFORMATION

CASING SIZE: 8

CASING TYPE: PVC

CASING DEPTH: 20

CASING CEMENT: YES

TOP ANODE: 225

BOTTOM ANODE 340

INDIVIDUAL ANODE DEPTHS 225,235,270,280,290,300,310,320,330,340

AMOUNT OF COKE: 2500

WATER INFORMATION

WATER DEPTH (1): 160

WATER DEPTH (2): NA

CEMENT PLUGS: NA

OTHER INFORMATION

GAS DEPTH: NA

VENT PIPE DEPTH 360

TOP OF VENT PERFORATIONS: 200

REMARKS: G/B DRILLED 7/97

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

PPCO.GROUNDBED LOG

PHILLIPS PETROLEUM CO.			DEEP WELL CATHODIC PROTECTION GROUNDBED LOG—DATA SHEET										
DRILLED BY: (DRILLER'S NAME AND COMPANY) <i>Jack Ledbetter</i> <i>Tierra Dynamic</i>													
LOCATION NAME: <i>SS 30-5 #52M</i>						DATE DRILLED: <i>7-2-77</i>							
LEGAL LOCATION: <i>Sec 13 - 30-5W</i>						SIZE AND TYPE OF CASING: <i>8" PVC</i>							
PPCO ID NO. (FM NO.) <i>607</i>						DEPTH OF CASING: <i>20'</i>							
TOTAL DEPTH: <i>360'</i>						COKE: (CIRCLE) <i>PETR.</i> OR <i>MET.</i> AMOUNT: <i>2500</i> LBS.							
DIAMETER OF HOLE: <i>6 3/4</i>						TYPE OF ANODES: <i>Anode 6</i>							
COUNTY: <i>Rio Arriba</i>													
									COMPLETION INFORMATION:				
DEPTH FT.	LOG	ANODE	DEPTH FT.	LOG	ANODE	DEPTH FT.	LOG	ANODE	WATER DEPTH	VENT PPE PERFS	ISOLA- TION PLUGS		
100	1.5		265	2.1		430			1) 160	TOP:	1)		
105	1.4		270	1.8	8	435			2)	BTM.:	2)		
110	1.4		275	1.4		440			ANODE#	DEPTH	OUTPUT NO COKE	OUTPUT COKED	
115	1.8		280	1.8	7	445							
120	1.9		285	1.9		450			1	340	2.0	5.0	
125	2.0		290	1.7	6	455			2	330	2.0	5.4	
130	2.0		295	2.1		460			3	320	1.7	5.8	
135	2.0		300	2.3	5	465			4	310	2.1	6.5	
140	1.7		305	2.1		470			5	300	2.2	6.9	
145	1.4		310	2.1	4	475			6	290	1.8	7.0	
150	1.1		315	2.1		480			7	280	1.8	7.0	
155	1.0		320	1.9	3	485			8	270	1.9	6.5	
160	.8		325	1.7		490			9	235	2.0	6.0	
165	.8		330	2.0	2	495			10	225	1.8	5.8	
170	.8		335	2.0		500			11				
175	1.1		340	2.0	1	505			12				
180	1.1		345	1.0		510			13				
185	1.5		350	.8		515			14				
190	1.8		355	T.D.		520			15				
195	1.6		360			525			16				
200	1.6		365			530			17				
205	1.7		370			535			18				
210	1.7		375			540			19				
215	1.9		380			545			20				
220	2.0		385			550			21				
225	1.8	10	390			555			22				
230	1.8		395			560			23				
235	1.9	9	400			565			24				
240	1.6		405			570			25				
245	1.7		410			575			26				
250	1.4		415			580			27				
255	1.2		420			585			28				
260	1.5		425			590			29				
LOGGING VOLTS: <i>11.40</i>						VOLTAGE SOURCE: <i>Auto</i>							
TOTAL AMPS: <i>14.6</i>						TOTAL G/B RESISTANCE: <i>.78</i>							
REMARKS:													