Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMEN 707

FÖRM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

BUREAU OF LAND MANAGEMENTO MAR -5 AM II: 105. Lease Designation and Serial No NOG-9309-1250 SUNDRY NOTICES AND REPORTS ON WELLSEGEIVED If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different regretor. The state of the Use "APPLICATION FOR PERMIT - -" for such proposals DIST. 3 SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well Gas 8. Well Name and No. Other Gracia Navajo 5K No. 2S 2. Name of Operator Pro NM Energy, Inc. 9. API Well No. 30-045-33471 3. Address and Telephone No. 460 St. Michael's Dr., Suite 402 Santa Fe, NM 87505 (505) 988-4171 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) **Basin Fruitland Coal** 11. County or Parish, State 1275' FNL & 1620' FWL Section 5, 125N, R11W San Juan County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Change of Plans Notice of Intent Abandonment Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-off Final Abandonment Notice Altering Casing Conversion to Injection Cementing Report Dispose Water (Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Pressure tested surface casing and BOP to 500 psi for 30 min. - held OK. Drilled 6 1/4" hole to \$1400' KB. Ran 33 jts of 4 1/2", 10.5#, J-55 casing. Casing landed at 1392' KB. Cemented with 100 sx (206 cf) of Type 5 cement containing 2% Sodium Metasilicate and 1/4 #/sk cello flakes. Tailed in with 100 sx (119 cf) of Type 5 cement containing 2% CaCl and 1/4 #/sk cello flakes. Did not circulate cement to surface and will run temperature survey to determine cement top. 14. I hereby certify that the foregoing is true and correct Dava J. Duluenthal 3/2/2007 Date (This space for Federal or State office) Approved by Date Conditions of approval, if any:

Report date reached TD

fictitious or fraudulent statements or representations as to any matter within its jurisdiction

nwocd &

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false

TE SALVETS COPICE