

3710

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

30-045-22124

Operator Meridian Oil Inc. Location: Unit D Sec. 12 Twp 31 Rng 11

Name of Well/Wells or Pipeline Serviced _____

LAWSON #1A

Elevation _____ Completion Date 4-26-93 Total Depth 465' Land Type F

Casing Strings, Sizes, Types & Depths 4 1/2" SET 99' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 19 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

10 SACKS of cement

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. 100' fresh

Depths gas encountered: 480'

Ground bed depth with type & amount of coke breeze used: 465'

7000 lbs 60 SACKS Loresco type Saw 20 SACKS Ashbury

Depths anodes placed: 450, 440, 425, 415, 405, 395, 385, 375, 365, 350, 340, 300, 290, 280, 210

Depths vent pipes placed: 465'

Vent pipe perforations: Bottom 350'

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.