

RCVD MAR 12 2007
OIL CONS. DIV.
DIST. 3

submitted in lieu of Form 3160-5
**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit A (NENE), 20' FNL & 370' FEL, Section 9, T27N R6W, NMPM

5. Lease Number
NMSF-079049
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name

8. San Juan 28-6 Unit
Well Name & Number

9. San Juan 28-6 Unit #205E
API Well No.

30-039-30120

10. Field and Pool

Basin Dakota

11. County and State
Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans <input checked="" type="checkbox"/> Other - Spud
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

Spud
3/1/07 MIRU Aztec 711. RIH w/12 1/4" bit. Drill ahead to 285'. Circ hole. RIH w/6 jts 95/8" 32.3# H-40 casing set @ 277'. RU to cement. Pumped Scavenger 10 sx(57cf - 10 bbls) Type III Cement w/3% CaCl2, & .25 #/sx Cello-flakes. Bumped plug & displaced w/20 bbls FW. No cement to surface. 3/2/07

3/2/07 Jim Foder contacted Jim Lovato (BLM) and notified that cement did not circulate to surface. Request to pump approx. 225 sx of cement & top out w/1" pipe. Verbal approval given to proceed by J. Lovato on 3/2/07.

3/2/07 RIH w/1" pipe, tag TOC @ 100'. Pumped 200sx(256 cf - 46 bbls) Type III Cement w/3% CaCl2, & .25 #/sx Cello-flakes Down backside thru 1" pipe, no cement to surface. Pumped 5sx(6 cf - 1 bbls) Type III Cement w/3% CaCl2 & .25 #/sx Cello-flakes, thru 1" pipe. Circ. 1bbl cement to surface. Pull 1" pipe. WOC. NU BOPE. PT casing to 600 psi 30/min. - good test.

APD/ROW

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 3/5/07

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date MAR 08 2007

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON FIELD OFFICE
BY [Signature]

NMCCD