District I 1625 N. French Dr., Hobbs, NM 88240 District III
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or	Below-0	Grade Tank	Registration	or Closure

Is pit or below-grade tank covered by a "general plan"? Yes No RCVD FEB27'07			
Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank OIL CONS. DIV.			
Operator: BP America Production Company Telephon	e: <u>(505)326-9200</u> e-mail address:		
Address: 200 Energy Ct, Farmington, NM 87401		DIST. 3	
Facility or well name: TAPP LS #1A API #: 30	0045 23700 U/L or Qtr/Qtr C	Sec 27 T 28 NR 8 W	
County: San Juan Latitude	Longitude	NAD: 1927 ☐ 1983 🔀	
Surface Owner: Federal 🗷 State 🗌 Private 🗀 Indian 🗋			
Pit	Below-grade tank		
Type: Drilling Production Disposal	Volume:bbl Type of fluid:		
Workover Emergency	Construction material:		
Lined Unlined	Double-walled, with leak detection? Yes 11 fng	explain why not.	
Liner type: Synthetic Thicknessmil Clay	/ V /		
Pit Volumebbl			
	Less than 50 feet	(20 points)	
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)	
high water elevation of ground water.)	100 feet or more	(0 points)	
	Vec	(20 :)	
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)	
water source, or less than 1000 feet from all other water sources.)	No	(0 points)	
	Less than 200 feet	(20 points)	
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)	
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)	
	Popling Searce (Total Points)		
	Ranking Score (Total Points)		
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's		• * * * * * * * * * * * * * * * * * * *	
your are burying in place) onsite 🛛 offsite 🗌 If offsite, name of facility_		=	
remediation start date and end date. (4) Groundwater encountered: No 🕍 Y	es 🔲 If yes, show depth below ground surface	ft. and attach sample results.	
(5) Attach soil sample results and a diagram of sample locations and excavat	ions.		
Additional Comments:			
See Attached Documentation			
•			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines [3], a general permit [1], or an (attached) alternative OCD-approved plan [1].			
Andrew Constitution of Sense and Sense and Sense and Sense and Cattached) and institute Och-approved plan			
Date:11/01/2005			
Printed Name/Title			
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.			
Approval: PYTTY OR & GAS INSPECTOR, OST			
Printed Name/Title	Signature Both Hall	Date: FEB 2 7 2007	
	Ka US - U William	Dutt	

BLAGG ENGINEERING, II P.O. BOX 87, BLOOMFIELD, N (505) 632-1199	
FIELD REPORT: PIT CLOSURE VERIFIC	
LOCATION: NAME: TAPP LS WELL #: 1 A TYPE: DE	/ I DATE EINICHED: >1 - 121 - C)
QUAD/UNIT: C SEC: 22 TWP: 28N RNG: 8W PM: NM CNTY: SJ	ST: NM
QTR/FOOTAGE: 790/N/1560W NEINW CONTRACTOR: FLINT	SAM) SPECIALIST: JCL
EXCAVATION APPROX. 24 FT. x 24 FT. x 5 FT. D	. 🗻
DISPOSAL FACILITY: ON SITE REMEDIATION	ON METHOD:
LANDUSE: RANGE - BLM LEASE: ALMSF 0784	199 FORMATION: MV
	FT. N 56°E FROM WELLHEAD.
DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000	NEAREST SURFACE WATER:
NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM	DVM CALIB. READ. = <u>\$3.2</u> ppm
SOIL AND EXCAVATION DESCRIPTION.	OVM CALIB. GAS = 100 ppm RF = 0.52
	IME: <u>0905</u> am/pm DATE: <u>8-8-03</u>
SOIL TYPE: (SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER SOIL COLOR:	
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COH	HESIVE
CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIC	GHLY PLASTIC
DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD	CLOSED
MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: (ES) NO EXPLANATION -	
HC ODOR DETECTED: (YES NO EXPLANATION	
ADDITIONAL COMMENTS: EARTHEN PIT ON SANDSTONE B	BOCKROCK SURFACE STRUNGLY
BEORDER IMPACTED W/ HC. USE BACKHOE T For SAMPLE	O SCRAPE SS. JURPINE
FIELD 418.1 CALCULA	ATIONS
SCALE SAMP. ID LAB NO. WEIGHT (g) ml	L FREON DILUTION READING CALC. (ppm)
0 FT	
	PIT PROFILE
→ PIT PERIMETER OVM	FILENOPILE
READING	
SAMPLE FIELD HEADSPACE ID (ppm)	
2@ 5' 440	
3@ 5 385	€ 24 →
A 24' THZ A 5@	<u>, 4</u>
	A
	A 4' 5
TH3 LAB SAMPLES	
LAB SAMPLES SAMPLE ANALYSIS TIME	
LAB SAMPLES SAMPLE ANALYSIS TIME FILES TPHISTER 1205	4 5
LAB SAMPLES SAMPLE ANALYSIS TIME THE TO THE LEGS WELL BOTH MISSO	FIRM BEDROCK
TH3 LAB SAMPLES SAMPLE ANALYSIS TIME TH 2 5 TPM/STEL 1205 P.D. = PIT DEPRESSION; B.G. = BELOW GRADE; B = BELOW T.H. = TEST HOLE; ~ = APPROX; T.B. = TANK BOTTOM	FIRM BEDROCK

revised: 09/04/02

bei1005C.skf



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Dehy/Prod TH #2 @ 5'	Date Reported:	08-11-03
Laboratory Number:	26285	Date Sampled:	08-08-03
Chain of Custody No:	11229	Date Received:	08-08-03
Sample Matrix:	Soil	Date Extracted:	08-11-03
Preservative:	Cool	Date Analyzed:	08-11-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	114	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	114	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Tapp LS 1A.

Analyst C. Q

Mistine m Waters
Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Dehy/Prod TH #2 @ 5'	Date Reported:	08-11-03
Laboratory Number:	26285	Date Sampled:	08-08-03
Chain of Custody:	11229	Date Received:	08-08-03
Sample Matrix:	Soil	Date Analyzed:	08-11-03
Preservative:	Cool	Date Extracted:	08-11-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	165	1.8
Toluene	806	1.7
Ethylbenzene	319	1.5
p,m-Xylene	1,200	2.2
o-Xylene	601	1.0
Total BTEX	3,090	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98 %
	1,4-difluorobenzene	98 %
	Bromochlorobenzene	98 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Tapp LS 1A.

Analyst C. Oglina

Mistine Mucheles
Review