

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

1. **Type of Well**  
GAS

2. **Name of Operator**  
ConocoPhillips

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit B (NWNE) 15' FNL & 2435' FEL, Sec. 26, T28N, R7W, NMPM

5. **Lease Number**  
SF-079290
6. **If Indian, All. of Tribe Name**
7. **Unit Agreement Name**  
San Juan 28-7 Unit
8. **Well Name & Number**  
SaN Juan 28-7 Unit 223F
9. **API Well No.**  
30-039-27257
10. **Field and Pool**  
Basin Dakota/Blanco MV
11. **County and State**  
Rio Arriba Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA****Type of Submission**

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

**Type of Action**

☐ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☒ Other - Casing Report

RCVD APR 3 2007

OIL CONS. DIV.

**13. Describe Proposed or Completed Operations**

3/14/07 MIRU HP 281. PT casing to 600# 30/min - good test. RIH w/8 3/4" bit, tagged @ 210'. D/O cement & ahead to 3605' intermediate. RIH w/86 jts 7" 20# J-55 ST & C casing set @ 3640'. Circ hole. RU to cement. 3/25/07 Pumped pre-flush of 20 bbls mud flush. **Lead-pumped** 690sx(1470cf-261bbls) Premium Lite Cement w/3% CaCl, 8% Bentonite, .25 #/sx Cello-flakes, .4% FL-52A, 5 #/sx LCM-1, & .4% Sodium Metasilicate. **Tail-** pumped 170sx(235cf-42bbls) Type III Cement w/1% CaCl, .25 #/sx Cello-flakes, .2% FL-52A. **Dropped plug & displaced** w/146 bbls FW. No cement to surface. Plug down @ 0000 hrs.

3/26/07 Cement did not circ to surface on 7" casing. Called Steve Mason (BLM). Temp. log ran and results showed TOC @ 1125'. Shoe is @ 3460'. Verbal approval from Steve Mason to proceed.

3/26/07 PT 7" casing to 1500# 30/min - good test. RIH w/6 1/4" bit. D/O cement & ahead to 7824' (TD). TD reached on 3/27/07. RIH w/26 jts 4 1/2" 11.6# J-55 ST & C, & 162 jts 4 1/2" 10.5# J-55 ST & C casing set @ 7821'. RU to cement. 3/28/07 Pumped pre-flush of 10 bbls vis gel/2 Bbls H2O. Pumped 315sx(624cf- 111bbls) Premium Lite HS FM Cement w/.3% CD-32, .25 #/sx Cello-flake, 1% FL-52A, 6.25 #/sx LCM-1. **Dropped plug & displaced.** Bumped plug @ 0325 hrs. ND BOP. RD RR @ 1200 hrs 3/29/07

Report TOC and PT on next sundry

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 3/30/07

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

ACCEPTED FOR RECORD

APR 02 2007

FARMINGTON FIELD OFFICE