

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit L (NWSW) 2100' FSL & 805' FWL, Sec. 32, T30N, R10W, NMPM

5. Lease Number
NMSF-078205
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name

8. Well Name & Number

Stewart A Com LS #2F
9. API Well No.

30-045-33934

10. Field and Pool

Blanco Mesa Verde/Basin Dakota

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

3/15/07 RIH w/8 3/4" bit, tag cement @ 180'. D/O cement & ahead to 4295' intermediate. RIH w/93 jts 7" 20# J-55 ST & C casing & 9 jts 7" 23# LT & C casing set @ 4290'. RU to cement. 3/19/07 pumped pre-flush of 10 bbls FW/10 bbls MC 11/10 bbls FW. Pumped Scavenger 19sx (57cf-10bbls) Premium Lite Cement w/8% Bentonite, 3% CaCl2, .4% SMS, .4% FL-52, .25 #/sx Cello-flakes, & 5 #/sx LCM-1. Lead- pumped 501 sx(1067cf-190bbls) Premium Lite Cement w/8% Bentonite, 35 CaCl2, .4% SMS, .4% FL-52, .25 #/sx Cello-flakes, & 5 #/sx LCM-1. Tail- pumped 216 sx(298cf-53bbls) Type III Cement w/1% CaCl2, .2% FL-52, .25 #/sx Cello-flakes. Dropped plug & displaced w/172 bbls FW. Circ 60 bbls cement to pit. Bumped plug. Plug down @ 02:01.

3/20/07 PT 7" casing to 1500# 30/min- good test. RIH w/6 1/4" bit. D/O cement & ahead to 6869' (TD). TD reached on 3/21/07. Circ hole. RIH w/1 jts 4 1/2" 11.6# J-55 & 164 jts 4 1/2" 10.5# J-55 casing set @ 6868'. RU to cement. 3/22/07 Pumped pre-flush of 10 bbls gel H2O/ 5 bbls H2O. Pumped Scavenger 9 sx(27cf-5bbls) Cement w/.3% CD-32, .25 #/sx Cello-flakes, 1% FL-52, & 6.25 #/sx LCM-1. Pumped 181 sx (358cf-64bbls) Premium Lite HS FM Cement w/.3% CD-32, .25 #/sx Cello-flakes, 1% FL-52, & 6.25 LCM-1. Dropped plug & displaced w/ 110 bbls FW. Bumped plug. Plug down @ 21:00 hrs. ND BOP. RD. RR @ 03:00 hrs 3/23/07.

The casing PT & TOC will be conducted by the completion rig and results shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 3/29/07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD

APR 02 2007

FARMINGTON FIELD OFFICE