

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(See other in-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NMSF-079290B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

San Juan 28-7 Unit

7. UNIT AGREEMENT NAME

San Juan 28-7 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 28-7 Unit #222F

9. API WELL NO.

30-039-30024

10. FIELD AND POOL OR WILDCAT

Basin Dk/Blanco MV

11. SEC., T., R., M. OR BLOCK AND SURVEY
OR AREA

Sec. 26 T28N R7W, NMPM

12. COUNTY OR
PARISH

Bio Arriba

13. STATE

New Mexico

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

16. DATE T.D. REACHED

17. DATE COMPL. (Ready to prod.)

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)

19. ELEV. CASINGHEAD

1/27/07

2/7/07

4/3/07

GL 6613'

KB 6628'

20. TOTAL DEPTH, MD & TVD

7801'

21. PLUG, BACK T.D., MD & TVD

7796'

22. IF MULTIPLE COMPL.,
HOW MANY*

2

23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesa Verde 4844' - 5880'

25. WAS DIRECTIONAL
SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Cement Bond Log/Gamma Ray Casing Collar

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" H-40	32.3#	234'	12 1/4"	surface; 184ax (247 cf)	20 bbls
7" L-80	23#	3634'	8 3/4"	surface; 387ax 53.7 (1173 cf)	30 bbls
4 1/2" L-80	11.8#	7800'	6 1/4"	TOC 2338'; 330ax (663 cf)	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	7715'	

30. TUBING RECORD

PERFORATION RECORD (Interval, size and number)	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
01SPF PLO/LMF 5262' - 5880' = 30 holes UMF/CH - 4844' - 5172' = 30 holes Total Holes = 65	5282' - 5880' Spearhead 10 bbls 15% HCL Acid, pumped 19845 gal 60Q Slickwater/Foam Pad, pumped approx. 100000# 20/40 Brady Sand. Displaced w/80 bbls. 4844' - 5172' Spearhead 10 bbls 15% HCL Acid, Pumped 10050 gal 60Q Slickwater/Foam pad. Pumped approx 100000# 20/40 Brady Sand. Displaced w/33 fld bbls 24000 SCF.

31. PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping-size and type of pump)	WELL STATUS (Producing or shut-in)
SI	Flowing	SI
DATE OF TEST	HOURS TESTED	CHOKE SIZE
3/29/07	1	1/2"
FLOW. TUBING PRESS.	CASING PRESSURE	24-HOUR RATE
250#	SI - 480#	0
		1650 mcf/d

32. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

33. LIST OF ATTACHMENTS

This will be a Basin Dakota/Mesa Verde well being DHC per order # 2445AZ

34. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Mary J. Menden TITLE Regulatory Technician DATE 4/10/07

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

APR 12 2007

FARMINGTON FIELD OFFICE

Ojo Alamo	2338'	2453'	White, cr-gr ss.	Ojo Alamo	2338'
Kirtland	2453'	2923'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2453'
Fruitland	2923'	3327'	Dk gry-gr carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	2923'
Pictured Cliffs	3327'	3543'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3327'
Lewis	3543'	4050'	Shale w/siltstone stringers	Lewis	3543'
Huerfanito Bentonite	4050'	4266'	White, waxy chalky bentonite	Huerfanito Bent.	4050'
Chacra	4266'	4970'	Gry fn grn silty, glauconitic sd stone w/drck gry shale	Chacra	4266'
Mesa Verde	4970'	5118'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	4970'
Menefee	5118'	5525'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5118'
Point Lookout	5525'	6007'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation.	Point Lookout	5525'
Mancos	6007'	6795'	Dark gry carb sh.	Mancos	6007'
Gallup	6795'	7496'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Gallup	6795'
La Ventana	XXXX	XXXX	Wt to lt buff to med grn sl carb bent	Greenhorn	7496'
Greenhorn	7496'	7555'	Highly calc gry sh w/thin lmst.	Graneros	7555'
Graneros	7555'	7595'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	7595'
Dakota	7595'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		