

DATE: 5/8/96DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc. Location: Unit G Sec. 34 Twp 28 Rng 09

Name of Well/Wells or Pipeline Serviced _____

Storey C #11Elevation 6824 Completion Date 5/8/96 Total Depth 491 Land Type FCasing Strings, Sizes, Types & Depths 5/7 Set 59' of 8" PVC Casing.No Gas, Water, or Boulders Were Encountered During Casing.If Casing Strings are cemented, show amounts & types used CementedWITH 15 SACKS

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONEDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT FRESH WATER AT 360'Depths gas encountered: NONEGround bed depth with type & amount of coke breeze used: 491' Depth.Used 130 SACKS OF Asbury 218R (6500#)Depths anodes placed: 475, 465, 455, 445, 435, 425, 415, 405, 395, 385, 375, 365, 355, 345, 335, 325, 315, 305, 295, 285, 275, 265, 255, 245, 235, 225, 215, 205, 195, 185, 175, 165Depths vent pipes placed: SURFACE TO 491'Vent pipe perforations: BOTTOM 360'

Remarks: _____

RECEIVED
FEB 19 1997OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPSS 2915-W D/L NAME (S), NUMBER (S) Storey C #11
 -Q 2I15 TOTAL VOLTS 11.77 AMPS 19.3 OHMS .610 DATE 5/8/96 NAME JOHN L. MOSS
 REMARKS (NOTES FOR CONSTRUCTION LOG)

Driller Reported DAMP AREAS AT
 70, 200, 260, AND WATER AT 360. INSTALLED 491' OF 1" PE
 VENT PIPE, WITH THE BOTTOM 360' PERFORATED. CORRE
 Breeze To 115.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE	"		ANODE	"		ANODE	"		ANODE	"
100			295			490	T.D.	491'	685		
105			300			495			690		
110			305			500			695		
115			310			505			700		
120			315		-13	510					
125			320			515					
130	3		325		-12	520					
135	3		330			525			1	475'	1.8
140	.4		335			530			2	465'	1.7
145	.4		340			535			3	455'	1.7
150	.4		345		-11	540			4	445'	3.0
155	1.0		350			545			5	435'	1.4
160	1.3		355		-10	550			6	425'	1.3
165	1.3	-15	360			555			7	415'	1.2
170	.9		365			560			8	405'	1.6
175	.4		370			565			9	395'	1.4
180	.3		375			570			10	385'	1.3
185	.3		380			575			11	375'	1.2
190	.2		385			580			12	365'	1.3
195	.1		390			585			13	355'	1.5
200	.3		395		-9	590			14	345'	3.0
205	.3		400			595			15	335'	1.7
210	.4		405		-8	600			16		
215	.2		410			605			17		
220	1.0		415		-7	610			18		
225	.9		420			615			19		
230	2.8	-14	425		-6	620			20		
235	2.8		430			625			21		
240	1.2		435		-5	630			22		
245	1.2		440			635			23		
250	1.0		445		4	640			24		
255	1.0		450			645			25		
260	1.1		455		3	650			26		
265	1.1		460			655			27		
270	1.1		465		2	660			28		
275	.9		470			665			29		
280	.9		475		1	670			30		
285	.9		480			675					
290	1.0		485			680					