

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 Copies to OCD Aztec Office)

MB-9

Operator: BLACKWOOD & NICHOLS CO. Location: Unit H, Sec. 27, Twp 31N, Rng 7W.

Name of Well/Wells or Pipeline Served NEBU 470, 70, 1, 217 30-045-27571, 30-045-24857,
30-045-60245, 30-045-25522

Elevation 6400' Completion Date 8-26-93 Total Depth 490' Land Type* Surface: F Mineral: SF-079003

Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C. - 100', 7-7/8" Open Hole

If Casing is cemented, show amounts & types used 20 sks Portland Zia I-II

If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. No water sample.

Depths gas encountered: N/A

Type & amount of coke breeze used: 129 sx Asbury Flo-Coke

Depths anodes placed: 130' - 453'

Depths vent pipes placed: 490' to 4' Above Ground Level

Vent pipe perforations: 110' - 490'

Remarks: Groundbed located 415' S 58° W of NEBU 470. WELLHEAD

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Signed by: James K. Aeb

Title: Operations Engineer

Date: 11/19/93

BLACKWOOD & NICHOLS CATHODIC GROUND BED DRILLERS REPORT

CP# MB-9 WELL# NEBU#470, #704#2.17

S 27 T 31 M R7

DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
5'					
10'					
15'					
20'					
25'	SAND				
30'	SAND				
35'					
40'					
45'	L				
50'	L				
55'	A				
60'	H				
65'	S				
70'					
75'	R				
80'	R				
85'	A				
90'	H				
95'					
100'	V				

DRILLER

INSPECTOR

44

DRYDEN & NICHOLS CATHODIC GROUND BED DRILLERS REPORT

7B-9 WELL# NEBU-470 #70, #217, #1

S 27 T 31 R

[illegible]

LER 12

INSPECTOR