

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit B Sec. 2 Twp 27 Rng 5

Name of Well/Wells or Pipeline Serviced San Juan 27-5 #7 and
San Juan 27-5 #110 30-039-07203, 30-039-20080

Elevation _____ Completion Date 3-26-96 Total Depth 387' Land Type F

Casing Strings, Sizes, Types & Depths 3-25-96 Set 57' of 8"
PVC Casing

If Casing Strings are cemented, show amounts & types used Casing was
Cemented with 14 sacks

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Damp at 140'. Fresh water at 210'

Depths gas encountered: None

Ground bed depth with type & amount of coke breeze used: 387'
5550 lbs Asbury

Depths anodes placed: ① 350', 340', 332', 325', 318', 310', 303', 296', 289', 260', 253', 246', 239', 232', ② 22'

Depths vent pipes placed: Surface to 387'

Vent pipe perforations: 87' to 387'

Remarks: No gas encountered during drilling of the hole

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2902-W	P/L NAME(S), NUMBER(S) San Juan 27-5 #7 & #110					
WO - ZE99 ZF19	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
		10.5	23.2	.45	3-26-96	David Ashworth
REMARKS (notes for construction log)						
600 135 Perf- 300' Dump at 140' 2.10' Main # 270 5550-111 Base Ash. Drilled 400' Logged 387						

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	2.5		490			685			
105			300	2.3		495			690			
110			305	1.7		500			695			
115			310	1.4	5	505			700			
120			315	2.1		510			ANODE	DEPTH	NO	FULLY
125			320	2.4	4	515			*		COKE	COK'D
130			325	2.4		520			1	350	1.8	3.8
135			330	1.9	3	525			2	340	1.9	4.1
140			335	2.0		530			3	332	1.9	4.3
145			340	1.9	2	535			4	325	2.4	5.1
150	1.5		345	1.6		540			5	318	2.5	5.1
155	1.9		350	1.8	1	545			6	310	1.6	3.9
160	2.3		355	1.5		550			7	303	2.0	4.3
165	1.6		360	.9		555			8	296	2.5	4.8
170	1.5		365	.9		560			9	289	2.1	4.1
175	1.7		370	.8		565			10	260	2.3	5.0
180	1.7		375	.7		570			11	253	2.4	5.6
185	1.5		380	.6		575			12	246	2.3	5.6
190	1.1		385	397-70		580			13	239	2.0	5.4
195	.9		390			585			14	232	2.7	6.3
200	1.2		395			590			15	225	2.9	6.1
205	.8		400			595			16			
210	.8		405			600			17			
215	1.3		410			605			18			
220	2.6	14	415			610			19			
225	2.9		420			615			20			
230	2.6	13	425			620			21			
235	2.1		430			625			22			
240	1.9	12	435			630			23			
245	2.3		440			635			24			
250	2.4	11	445			640			25			
255	2.4		450			645			26			
260	1.9	10	455			650			27			
265	.8		460			655			28			
270	.7		465			660			29			
275	.7		470			665			30			
280	.8		475			670						
285	1.1		480			675						
290	2.1	9	485			680						

DISTRIBUTION - original - permanent CPS FILE

COPY

- Division Corrosion Supervisor

COPY

- Region Corrosion Specialist