

DATE: 5/3/96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Mesa Verde Oil Co. Location: Unit K Sec. 7 Twp 30 Rng 4

Name of Well/Wells or Pipeline Serviced Parson #2

30-039-22083

Elevation 6692 Completion Date 5/3/96 Total Depth 391' Land Type F

Casing Strings, Sizes, Types & Depths 5/2/96, lot 58' of 8" PVC

Casing: No gas, water or boulders were encountered during casing.

If Casing Strings are cemented, show amounts & types used

Cemented with 12 sacks.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Driller reported a damp spot at 120'

and 300'. No sample was taken.

Depths gas encountered: None

Ground bed depth with type & amount of coke breeze used: 391' Depth

Used 104 sacks of Ashbury coke breeze { 50 lb sacks }

Depths anodes placed: 345, 334, 329, 321, 313, 305, 260, 250, 240, 230, 220, 210, 190, 130, 115'

Depths vent pipes placed: Surface to 391'

Vent pipe perforations: Bottom 280'

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2894-w		P/L NAME(S), NUMBER(S) Corson #2					
WD # 1H45 1H47	TOTAL	VOLTS 11.51	AMPS 30.7	- OHMS 37	DATE 5/3/96	NAME LSE	
REMARKS (notes for construction log) Drilled 400', logged 391'							
Driller reported a damp spot at 120' + 300'. No sample was taken.							
Installed 391' of 1" PE Vent pipe, with the bottom 280' perforated.							

DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	
100	1.1		295	1.0		490			685			
105	1.0		300	1.7		495			690			
110	1.1		305	1.3		500			695			
115	1.3	15	310	1.4	6	505			700			
120	1.0		315	1.3	5	510			ANODE	DEPTH	NO	FULLY
125	1.2		320	1.3		515			*		COKE	COKE'D
130	1.4	14	325	1.3	4	520			1	345	1.3	6.2
135	1.0		330	1.4	3	525			2	337	1.4	6.3
140	1.2		335	1.4		530			3	329	1.5	6.8
145	.9		340	1.4	2	535			4	321	1.3	6.5
150	.7		345	1.3	1	540			5	313	1.4	6.1
155	1.0		350	1.1		545			6	305	1.2	5.2
160	1.1		355	1.2		550			7	260	1.4	5.8
165	1.0		360	1.1		555			8	250	1.4	5.7
170	1.1		365	1.1		560			9	240	1.4	6.0
175	1.2		370	1.0		565			10	230	1.4	6.1
180	1.2		375	1.1		570			11	220	1.3	5.9
185	1.1		380	1.3		575			12	210	1.5	6.2
190	1.3	13	385	1.3		580			13	190	1.4	6.6
195	1.2		390	TD	391	585			14	130	1.5	7.0
200	1.0		395			590			15	115	1.5	6.6
205	1.2		400			595			16			
210	1.3	12	405			600			17			
215	1.3		410			605			18			
220	1.3	11	415			610			19			
225	1.3		420			615			20			
230	1.3	10	425			620			21			
235	1.3		430			625			22			
240	1.3	9	435			630			23			
245	1.2		440			635			24			
250	1.3	8	445			640			25			
255	1.3		450			645			26			
260	1.3	7	455			650			27			
265	1.2		460			655			28			
270	1.1		465			660			29			
275	1.0		470			665			30			
280	1.0		475			670						
285	1.0		480			675						
290	1.0		485			680						

DISTRIBUTION - original - permanent CPS FILE

COPY

- Division Corrosion Supervisor

COPY

- Region Corrosion Specialist