

DATE: 5-1-96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit N Sec. 30 Twp. 30 Rng. 4

Name of Well/Wells or Pipeline Serviced CARSON #3

30-039-22286

Elevation _____ Completion Date _____ Total Depth _____ Land Type _____

Casing Strings, Sizes, Types & Depths 60' of 8" PVC SURFACE

CASING

If Casing Strings are cemented, show amounts & types used Yes with

18 BAGS CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. Damp? 230'

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 451' deep with

6,000 lbs Asbury 218R

Depths anodes placed: 438, 429, 420, 411, 402, 355, 345, 335, 326, 300, 290, 280, 270

Depths vent pipes placed: 451' 260, 252

Vent pipe perforations: bottom 350

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					DATE	NAME
2895w	CARSON #3					5-1-96	MRW
WO #	TOTAL	VOLTS	AMPS	OHMS			
2N99		10.94	23.7	461			
REMARKS (notes for construction log)							
60' CASING 18 BAGS CEMENT							
N30-30-4 Drilled 460' LOGGED 451' Perforated 350'							
120 Asbury 21&R Damp 220'							

DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	
100			295	1.9		490			685			
105			300	2.0		495			690			
110			305	1.2		500			695			
115			310	.6		505			700			
120			315	.5		510			ANODE	DEPTH	NO	FULLY
125			320	.6		515			*		COKE	COK'D
130			325	1.8		520			1	438	2.6	5.4
135			330	2.4		525			2	429	1.9	4.7
140			335	2.6		530			3	420	1.9	4.6
145			340	2.6		535			4	411	1.9	4.6
150			345	2.5		540			5	402	1.9	4.5
155			350	2.4		545			6	355	2.0	4.5
160	1.3		355	1.9		550			7	345	2.6	4.6
165	1.5		360	1.5		555			8	335	2.7	5.8
170	.8		365	.5		560			9	326	2.1	4.6
175	.8		370	.3		565			10	300	2.1	5.3
180	.9		375	.6		570			11 x	290	2.1	5.7
185	.8		380	.9		575			12 x	280	2.2	6.0
190	.9		385	.7		580			13	270	2.5	5.1
195	.8		390	.8		585			14	260	2.4	5.2
200	.9		395	1.5		590			15	250	1.9	5.2
205	.7		400	1.8		595			16			
210	.6		405	1.9		600			17			
215	.9		410	1.8		605			18			
220	1.1		415	2.0		610			19			
225	1.0		420	1.8		615			20			
230	.9		425	1.9		620			21			
235	1.8		430	2.0		625			22			
240	1.6		435	2.4		630			23			
245	1.5		440	2.6		635			24			
250	1.7		445	2.3		640			25			
255	2.0		450	2.2	451	645			26			
260	2.3		455			650			27			
265	2.2		460			655			28			
270	2.4		465			660			29			
275	2.4		470			665			30			
280	2.0		475			670						
285	2.3		480			675						
290	2.0		485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist