

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit SW Sec. 19 Twp 32 Rng 14

Name of Well/Wells or Pipeline Serviced _____

UTE COM #25

Elevation _____ Completion Date 12/13/95 Total Depth 455' Land Type I

Casing Strings, Sizes, Types & Depths 12/11 Set 99' of 8" PVC CASING.

NO GAS, WATER, or Boulders were encountered during casing.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. NO LIVE WATER WAS ENCOUNTERED. Hole

MADE 150' OF FRESH WATER OVERNIGHT.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 455' Depth.

Used 117 SACKS OF ASBURY 218R (5850#)

Depths anodes placed: 440', 430', 420', 410', 400', 390', 380', 370', 325', 315', 305', 195', 170', 160', + 150'

Depths vent pipes placed: SURFACE TO 455'

Vent pipe perforations: BOTTOM 320'

Remarks: _____

RECEIVED

FEB 1 9 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPB# 2841-W P/L NAME(S), NUMBER(S) UTE Com #25
 -O Y323 TOTAL VOLTS 13.03 AMPS 22.4 - OHMS .582 DATE 12/13/95 NAME JOHN L. MOSS
 REMARKS (NOTES FOR CONSTRUCTION LOG)

Driller Reported Damp Areas,
 But no Live Water. Installed 455' of 1" PE Vent Pipe, with
 The Bottom 320' Perforated. Core Breeze To 115'. Hole Made
 150' of Water Duct Night.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE	"		ANODE	"		ANODE	"		ANODE	"
100			295			490			685		
105			300	1.2		495			690		
110			305	1.2		500			695		
115			310	1.2		505			700		
120			315	1.1	10	510					
125			320	1.2		515					
130	.2		325	.2	9	520					
135	.1		330	.2		525			1	440'	2.2
140	.2		335	.3		530			2	450'	2.6
145	.7		340	1.0		535			3	420'	2.7
150	1.7	15	345	.6		540			4	410'	2.0
155	1.1		350	.1		545			5	400'	1.3
160	1.2	14	355	.5		550			6	390'	1.8
165	1.2		360	.8		555			7	380'	1.4
170	1.0	13	365	1.4		560			8	370'	1.4
175	.5		370	1.4	8	565			9	325'	1.1
180	.6		375	1.2		570			10	315'	1.2
185	.9		380	1.2	7	575			11	305'	1.1
190	1.0		385	1.7		580			12	195'	1.1
195	1.1	12	390	1.6	6	585			13	175'	1.1
200	.9		395	1.1		590			14	160'	1.1
205	.9		400	1.3	5	595			15	150'	1.6
210	.9		405	1.4		600			16		
215	.8		410	2.2	4	605			17		
220	.5		415	2.3		610			18		
225	.8		420	2.6	3	615			19		
230	1.0		425	2.7		620			20		
235	.8		430	2.8	2	625			21		
240	.7		435	1.6		630			22		
245	1.0		440	2.0	1	635			23		
250	.6		445	2.2		640			24		
255	.4		450	2.2		645			25		
260	.4		455	T.D	455'	650			26		
265	.4		460			655			27		
270	.2		465			660			28		
275	.8		470			665			29		
280	.4		475			670			30		
285	.2		480			675					
290	.2		485			680					