30-039-26853

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

Name of Well/Wells or Pipeline Serviced SAN JUAN 28-6 UNIT #411 cps 2172w Elevation 6602'Completion Date 11/27/90 Total Depth 495' Land Type* P Casing, Sizes, Types & Depths 20' OF 8" FVC CASING If Casing is cemented, show amounts & types used 5 EACH 90LB BAGS OF SACKRETE. If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. 440' NO SMAPLE Depths gas encountered: N/A Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'	Operator MERIDIAN OIL INC.	Location: UnitK Sec. 30 Twp 28 Rng 6
Elevation 6602'Completion Date 11/27/90 Total Depth 495' Land Type* P Casing, Sizes, Types & Depths 20' OF 8" PVC CASING If Casing is cemented, show amounts & types used 5 EACH 90LB BAGS OF SACKRETE. If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. 440' NO SMAPLE Depths gas encountered: N/A Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'	Name of Well/Wells or Pipeline Servic	ed SAN JUAN 28-6 UNIT #411
Casing, Sizes, Types & Depths 20' OF 8" PVC CASING If Casing is cemented, show amounts & types used 5 EACH 90LB BAGS OF SACKRETE. If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. 440' NO SMAPLE Depths gas encountered: N/A Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'		cps 2172w
If Casing is cemented, show amounts & types used 5 EACH 90LB BAGS OF SACKRETE. If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. 440' NO SMAPLE Depths gas encountered: N/A Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'	Elevation 6602 Completion Date 11/27/90	Total Depth 495' Land Type* P
SACKRETE. If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. 440' NO SMAPLE Depths gas encountered: N/A Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'	Casing, Sizes, Types & Depths 2	20' OF 8" PVC CASING
If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. 440' NO SMAPLE Depths gas encountered: N/A Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'		types used 5 EACH 90LB BAGS OF
Fresh, Clear, Salty, Sulphur, Etc. 440' NO SMAPLE Depths gas encountered: N/A Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'	If Cement or Bentonite Plugs have bee	
Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'		•
Type & amount of coke breeze used: 5700 lbs. Depths anodes placed: 420', 410', 400', 390', 380', 370', 360', 350', 295', 285' Depths vent pipes placed: 500'	Depths gas encountered: N/A	
Depths vent pipes placed: 500'		5700 1bs.
	Depths anodes placed: 420', 410', 400', 3	90', 380', 370', 360', 350', 295', 285'
	Depths vent pipes placed: 500'	
Vent pipe perforations: 300'	Vent pipe perforations: 300'	SECEIAED
Remarks: _gb #1 MAY31 1991	Remarks: gb #1	MAY 3 1 1991
OIL CON. DIV		

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

^{*}Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.