

6 = 30-045-10494
13 = 30-045-10483
103 = 30-045-27283

4165

M.

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO**

Operator MERIDIAN OIL CO. Location: Unit SW Sec. 20 Twp. 31 Rng. 11

Name of Well/Wells or Pipeline Serviced Granier # 6 & # 13 & # 103

cps 4065w

Elevation 6033 Completion Date 7/17/90 Total Depth 300 ft. Land Type N/A

Casing Strings, Sizes, Types & Depths Set 60 ft. 8" PVC CEMENTED WITH
FIVE SACKS

If Casing Strings are cemented, show amounts & types used FIVE SACKS OF
PORTLAND CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 110 to 120 ft., no sample also water sand at 45-50 ft.
wash water 0 to 20 ft.

Depths gas encountered: N/A

Ground bed depth with type & amount of coke breeze used: 290 logged and 3000 lbs of Ashbury Petroleum Coke used.

Depths anodes placed: 265, 255, 245, 235, 225, 215, 205, 195, 185, 175

Depths vent pipes placed: 290 ft. 1" vent pipe

Vent pipe perforations: 190 ft. perforated

Remarks: gb #1

RECEIVED

MAY 31 1991

OIL CON. DIV
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.