RCVD MAY3'07 **NIL CONS. DIV.**

NEW MEXICO OIL CONSERVATION DIVISION

This form is not to be used for

Completion

Lower Completion

Hour, Date, Shut-In

DIST. 3

Revised June 10, 2003 NORTHWEST NEW MEXICO PACKER LEAKAGE TEST Well **DEVON ENERGY** No. 19M Operator Lease Name Location Of Well: Unit Letter f Sec 20 Twp 30-N Rge 7-W API # 30-0 39-30150 Name of Reservoir or Pool Type of Prod. Method of Prod. Prod. Medium (Oil or Gas) (Flow or Art. Lift) (Tbg. Or Cag.) Upper PICTURED CLIFFS FLOW GAS CASING Completion Lower DAKOTA GAS FLOW TUBING Completion Pre-Flow Shut-In Pressure Data Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Upper 4/5/2007 @1200pm waiting on C-104 Completion 197psi yes Hour, Date, Shut-In Length of Time Shut-In SI Press, Psig Stabilized? (Yes or No) Lower Completion 4/5/2007 @1200pm 16days 1922psi yes Flow Test No. 1 1200hr 4-20-2007 Zone Producing (Upper or Lower): Commenced at (hour, date)* Remarks Prod. Zone Time Lasped Time Pressure Lower Compl. Temp. (Hour, Date) Since* Upper Compl. 00hrs 4-20-20 197psi 1922psi initial flow rate 2500mcf 4/21/2007 194 1144mcf/d 24 198 4/22/2007 1174mcf/d 48 200реі 158 4/23/2007 72 120 918mcf/d 200psi 4/24/2007 96 95 769mcf/d 196psi 198psi 4/25/2007 120 78 721mcf/d **Production Rate During Test** Oil: BOPD based on Bbls. In Hrs. ____ Grav. ___ MCFPD; Test thru (Orifice or Meter): Mid-Test Shut-In Pressure Data Hour, Date, Shut-In SI Press. Psig Stabilized? (Yes or NO) Upper Length of Time Shut-In

(Continue on reverse side)

SI Press. Psig

Stabilized? (Yes or NO)

Length of Time Shut-In

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Flow Test No. 2

Commenced at	t (hour, date)*		Zone Proc	ducing (Upper or L	ower):	
Time	Lasped Time	Pre	sure	Prod, Zone	Remarks	
(Hour, Date)	Since*	Upper Compl.	Lower Compl.	Temp.		
ĺ						
					 	
		1				
		İ				
					-	
					1	
Production Ra	te During Test	<u> </u>			-	
	Ü					
Oil:	BOPD base	d on	Bbls. In	Hrs.	Grav.	GOR
Gas:		MCFPD; Test thru	(Orifice or Meter):			
Remarks:						
I hamaha aantifi	y that the information	housin sontained is t	min and sampless to	the best of my lene	uladas	
i nercely certify	y that the information	nerem contained is t	AART	the best of my kno	wieuge.	
		MAY 0 3	Zuni			
Appoved		6.16.01	20	Op	erator	DEVON ENERGY
	il Conservation Divisio	n .				DD (U. D. D. D. U. D.
	/ / ^	" a or last a				
	11 / 1/1//	04/04/07	i			0000
By /	4. Villa	wa		Title	lease operator	E. Edward
· t	DEBLITY On	A.C. 1010000000				
Title	defail of F C	as inspector,	D15T. #3	E-mail	Address edwin.e	edwards@DVN.com
_	_			•		
				Date		May 3, 2007

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).