This form is not to be used for reporting packer leakage tests in Southeast New Me

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

in Southeast New Mexico	NORTHWEST NEW MEXICO I	PACKER LEAKAGE TES	T Revised June 10, 2003
Operator Williams #	Production + Exploration	Lease Name Rosci	Unit. No. 145 my PC

	_	<u> </u>		
Location Of V	Well: Unit Letter Sec 16	6 Twp 3/1 Rge 1	API # 30-0 45	52910600
	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art, Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	P.C.	605	flow of	760
Lower Completion	MV.	Gas	Flour	76g,
	· · · · · · · · · · · · · · · · · · ·	-Flow Shut-In Pressure Da	ita	
Upper Completion	Hour, Date, Shut-In 16:40 4/10/07	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	10:70 12/00/		<u> </u>	Yes

Hour, Date, Shut-In Lower Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion Flow Test No. 1 Zone producing (Upper or Lower): lores Commenced at (hour, date)*

				10410			
Time	Lapsed Time		<u>essure</u>	Prod. Zone	Remarks		
(Hour, Date)	Since*	Upper Compl.	Lower Compl.	Temp.	The state of the s		
14:30	96 pm.	0	181	460	upper zone logged of		
· .					RCVD APR25'07		
		,	,		OIL CONS. DIV.		
					DIST. 3		
roduction rate	during test						

______BOPD based on ______Bbls. In _____ Hrs. _____ Grav. ____ GOR ____

425 MCFPD; Test thru (Orifice or Meter): Or, Fice Meter

Mid-Test Shut-In Pressure Data Upper Hour, Date, Shut-In Length of Time Shut-In Stabilized? (Yes or No) SI Press. Psig Completion Lower Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion

(Continue on reverse side)

(

RCVD MAY14'07 OIL CONS. DIV.

Flow Test No. 2

Commenced at (hour, date)**				Zone producing (U	one producing (Upper or Lower):		
Time	Lapsed Time	Pressure		Prod. Zone	Remarks	,	
(Hour, Date)	Since**	Upper Compl.	Lower Compl	Temp.			
·							
							
				•			_
		İ			1		
		-					
	<u> </u>						
5 1	<u> </u>		<u> </u>		``		
Production rate	during test	•	D1.1 I	77		COD	
On:	BOPD base	a on(Oni	_Bois. in	Hrs	Grav	GOR	—
Remarks:	MCFF	D; Test thru (On:	nce or Meter): _				—
Nemaiks.							
I hereby certify	that the information	tion herein contai	ned is true and o	complete to the bes	t of my knowledge	3.	
		MAY	1 4 2007 20	_	-		
Approved			20	_ Operator //	MENNY SO	ALUE MUN	_
New Mexico C	Dil Conservation I	Division		_ /		Swettman	۲-
. 1	/	-		Ву (L
p., A	Villanue	100		Title (١
Бу	V Da anus			nue(•		٦
Title		DEPUTY OIL & GAS	INSPECTOR, DIST	E-mail Add	ress)
				/			≠ ↑
				Date			1
		Northwes	t New Mexico Packe	r Leakage Test Instructi	ons		J

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).