District I 1625 N. French Dr., Hobbs, NM \$5240 Dindict IV 1220 S. St. Francis Dr., Santa Fe, Ned 87585

State of New Mexico Energy Minerals and Natural Resources

FORM C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. MOCD District Offi

Santa Fe, NM 87505

Pit or Classific Grade Tank Registration or Classific Is pit or below-grade tank covered by a "general plan"? Yes No K		
on Newbourne Dil as. 1505)593-5905 N/A NA		
Address: Box 5270 Holbs NM 8824/ Postage Pine Box 17 Fed. #1 APIS: 30-015-349/3 UR - Quide: P 300 17 T 205 125E County: Education N32'34'05.7' Language WIO4'30'06.9" NAID: 1907 11908 11		
Surface Owner; Policeal (1) State [] Private [] Sindian []		
PR Type: Drilling C Production Disposal	Makes straight from: Volume: Well Type of Shrisk: Construction material: Double-malled, with last detection? Yes The net, explains valay not.	
Westerner [] Brocagonery [] Linet [X Uniform []		
Liner type: Synthetic (A) Thickness /2 mil Chy [] Pit VolumeMd		·
Double to ground water (vertical distance from bottom of pit to sessent high water elevation of ground water.)	Lone than 50 flot 50 flot or more, but how then 100 flot 100 find or more 200 '	(20 prints) (10 prints) (0 prints)
Wellhood protection area: (Less than 200 feet from a private diametric water source, or loss than 1000 feet from all other water source.)	Yes No	(26 points) (6 points)
Distance to surface water: (heritoutal distance to all wellands, playes, imigation cannls, dischos, and personial and ophomena watercommon.)	Less then 200 first 200 first or meso, but has then 1000 first 2000 first or meso	(20 points) (10 points)
	Ranking Score (Total Points)	0
Hithis is a sil character. (1) Attach a diagram of the facility showing the pit's relationship to other equipment and trade. (2) Indicate disposal location: (check the cambe box if your are burying in place) easile official If official, same of facility N / A . (3) Attach a general description of responsible action taken including remediation start date and end date. (4) Groundwater encountered: No Yes If yes, show depth below ground surface N / A ft. and attach sample results. (5) Attach and sample require and a figure of sample locations and excessions. Additional Comments:		
I heady coully that the information above is tow and complete to the best of any knowledge and belief. I forther curify that the above described pit or below-grade teak has been/will be constructed or chancel accounting to PMOCD guidelines, if I a general purmit [], or an futtenhally alternative OCD-approved plan []. Date: 5/8/07 Printed Name/Title Dig Sta. (Ai Soul Service Hought Signature.) Your confliction and NMOCD approved of this application become not entire the explane of this by algorith the contents of the pit or tank contentions ground under or otherwise endanger public health or the explanation. Nor does it militare the expensive office any manifests with any other federal, state, or local investments.		
Approval: Printed Neue/Title	_ Alla Benne	5/11/07

Notify OCD 24 hours prior to beginning pit closure.

> Samples are to be obtained from pit area and analysis submitted to NMOCD prior to back-filling





SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: Mewbourne Oil Co.

WELL SITE: PINE BOX 17 Fed. #1

LEGAL DESCRIPTION: Unit P Sec /7 T20s R25e,

Eddy co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 150' X 150' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1800 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

LOCATION DIAGRAM

Mewbourne Oil, Pine Box 17 Fed. #1 API #30-015-34913 V-DOOR - South

