Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED					
OMB NO. 1004-0135					
Expires: November 30, 2000					

NM	10MI	2299

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS	7
Do not use ti	his form for	propo	sals to drill o	r to	re-enter a	n

Do not use this form for abandoned well. Use For	6 (If Indian, Allottee or Tribe Name					
SUBMIT IN TRIPLICATE -	Other instructions or	reverse side // >	<u> </u>	7 If Unit or CA/Agreement, Name and/or No		
Type of Well     Oil Well	A Company of the Comp	SEP 2003		8. Well Name and No.		
ConocoPhillips Company		OLE STATE	77	SJ 31-6 Unit #201A 9. API Well No.		
3a. Address	<b>73E</b>	hone No. (include are	a code)	30-039-27468		
5525 Highway 64, NBU 3004, Farmingt		<u> </u>	\$\frac{1}{2}	10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey I Unit O (SWSE), 660' FSL & 1500' FEL Section 1, T30N, R6W	<i>"</i>	Basin Fruitland Coal 11. County or Parish, State Rio Arriba, NM				
12. CHECK APPROPRIATE	BOX(ES) TO INDIC	ATE NATURE OF N	OTICE, REP			
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION					
Notice of Intent  X Subsequent Report	Acidize Alter Casing Casing Repair	Deepen Fracture Treat New Construction	Production Reclamatio			
Final Abandonment Notice	Change Plans  Convert to Injection	Plug and Abandon (**) Plug Back	Temporarii Water Disp	7 Castily report		
Describe Proposed or Completed Operation (clearly if the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. It testing has been completed. Final Abandonment Metermined that the final site is ready for final inspect 8/17/03 RIH w/8-3/4" bit & tagged hole. RIH w/7", 20#, J-55 casing bbls FW w/dye in last 10 bbls. P Chemical extender, 0.25#/sx Cello slurry) 50/50/G/POZ w/2% D029, 2% agent. Released wiper plug and d plug w/2000 psi @ 0036 hours 8/20 and cut off casing. Installed tr on next report.	polete horizontally, give subsuctormed or provide the Bonic fit the operation results in a resolution.)  I cement @ 186'. Do and set @ 2968'.  Pumped Lead - 430 suphane Flakes, & 0.  CC1C12, 5#/sx Gils  Itisplaced w/10 bbls  1/03. Circ. 71 sx c	rface locations and measual No. on file with BLM/F multiple completion or rec fter all requirements, inclu rilled out cement RU Schlumberger x (1122.3 cf - 19 2% Antifoam agent onite, 0.25#/sx ( FW & 108.4 bbls ement to surface.	t and the version of the completion in a ruding reclamation to the cement.  99.9 bbl slt. Tail - Cellophane Polymerize. RD Schlum	tical depths of all pertinent markers and zones. ubsequent reports shall be filed within 30 days new interval, a Form 3160-4 shall be filed once n, have been completed, and the operator has  formation to 2974'. Circ Pumped a preflush of 30 urry) Class G cement w/3% 100 sx (127 cf - 22.5 bbls Flakes & 0.2% Antifoam d Drilled water. Bumped berger. ND BOP, set slips		
14. I hereby certify that the foregoing is true and correct Name (Primed/Typed)	Patsy Clugston			ve Assistant ACCEPTED FOR RECORL		
- JUXUA (MGII)	S SPACE FOR FEDER	Date 8/21/0	_===			
Approved by	, J. AOL FOR FEDER	Title	CE USE	Date 5 2003		
Conditions of approval, if any, are attached. Approval o certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations the	those rights in the subject	nt or Office		ARIMINUTUR PIELD OFFICE		