submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RCUD MAY18'07 OIL CONS. DIV.

DIST. 3

	Sundry Notices and Reports on Wells 2007 16	AY 16	PM 2: 21
		5.	Lease Number
			V NMSF-080066
1.	Type of Well	6.1.	If Indian, All. or
	GAS 210 F	ABOU!	Tribe Name
ว	Name of Operator	7.	Unit Agreement Name
2.			
	ConocoPhillips		San Juan 30-5 Unit
		- 8.	Well Name & Number
3.	Address & Phone No. of Operator	0.	Well Librate of Linkshook
		_	San Juan 30-5 Unit 50G
_	PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
		_	30-039-30107
4.	Location of Well, Footage, Sec., T, R, M	10	Dield and Deal
I In	it I (NESE) 2200' FSL & 1100' FEL, Sec. 6, T30N, R5W, NMPM	10.	Field and Pool
Chit (1922) 2200 100 to 1100 122, occ. 0, 1301, 1200, 1011			Basin DK/BlancoMV
		11.	County and State
			Rio Arriba Co., NM
Bbl Cel: SM 01:4 H2C Cel: Cel: 5/12	I w/84 jts 7" 20# J-55 ST & C casing set @ 3636', stage tool set @ 2678'. RU to cement. 5/11/07 Pumps H2O. 1st Stage- Pumped Scavenger 19 sx(57cf-10bbls) Premium Lite Cement w/3T CaCl2, .4% Sod lo-Flake, 5% LCM-1. Lead- Pumped 81 sx(173cf-31bbls) Premium Lite Cement w/3% CaCl, .25#/Cel S. Tail- pumped 90 sx(124cf-22bbl) Type III Cement w/1% CaCl, .25 #/sx Cello-Flake, # .25 FL-52. El 45/12/07, opened DV tool w/2040@. Circ 30 bbls cement to surface. Circ hole. 2nd Stage- Pumped pt D/10 bbls H2O. Pumped Scavenger 19 sx(57cf-10bbls) Premium Lite Cement w/3% CaCl2, .4% Sodium lo-Flake, 5% LCM-1. Pumped 382 sx(814cf-145bbls) Premium Lite Cement w/3% CaC; 24% Sodium lo-Flake, & 5% LCM-1. Dropped plug & displaced. Plug down @ 06:50 hrs. 5/12/07. Circ 18 bbls cement w/3% CaC; 24% Sodium lo-Flake, & 5% LCM-1. Dropped plug & displaced. Plug down @ 06:50 hrs. 5/12/07. Circ 18 bbls cement w/3% CaC; 24% Sodium lo-Flake, & 5% LCM-1. Dropped plug & displaced. Plug down @ 06:50 hrs. 5/12/07. Circ 18 bbls cement lo-flow later w/3 bbls cement w/3 bbls cement later w/3 bbls cement w/3 bbls cemen	ium Met lo-Flake hisplaced e-flush on Metas Mtasili ent to su illed ahe @ 7945'	asilicat, .4% FL-52, .25 #/sx, 5 #/sx LCM-1, .4% FL-52, .4% I w/40 bbls H2O. Plug down @ of 10 bbls gel H2O/10 bbls ilicat, .4% FL-52, .25 #/sx cat, .4^ FL-52, .25 #/sx rface. Close DV tool w/2500#. ad to 7946' (TD) TD reached . RU to cement. 5/15/07 pumpe
Lite Hele	flush of 10 bbls Chem wash/2 bbls FW. Pumped Scavenger 9 sx(27cf-5bbls) Premium Lite Cement. Por HS FM Cement w/.25 #/sx Cello-Flake, .3% CD-32, 6.25 #/sx LCM-1, 1% FL-52. Dropped plug & did w/1320# @ 03:18 5/16/07. RD RR 5/16/07.		
Pres	sure Test & TOC will be done by the completion rig. Results will be shown on next report.		
14	I hereby certify that the foregoing is true and correct.		· — — — — — — — — — — — — — — — — — — —
Sig	ned Mucey W Montor Tracey N. Monroe Title Regulatory Technicia	<u> </u>	Date5/16/07
	is space for Federal or State Office use)		A/, TITUE TOO
	PROVED BY Title		Tate HOUSE IED HORRECO. D
Title	NDITION OF APPROVAL, if any: 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of nited States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		FW 17 257