

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NM-012641

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

RECEIVED
070 FARMINGTON NM Blanco 10B

9. API WELL NO.

30-045-33024 - 0051

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 26 T31N R8W, NMPM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:

OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

2007 MAY 11 PM 3:36

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐

2. NAME OF OPERATOR

ConocoPhillips

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface Unit N (SESW) 830' FSL, 1935' FWL

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO. DATE ISSUED

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

9114106 9/11/06

15. DATE SPUDDED 9/11/06

16. DATE T.D. REACHED 10/5/06

17. DATE COMPL. (Ready to prod.) 5/4/07

18. ELEVATIONS (DF, RKB, RT, BR, ETC.) GL 6259' KB 6272'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

5678'

21. PLUG, BACK T.D., MD & TVD

5659'

22. IF MULTIPLE COMPL., HOW MANY*

2

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesa Verde 4778' - 5634'

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Cement Bond Log/Gamma Ray Casing Collars

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" H-40	32.3#	219'	12 1/4"	surface; 75#x (122 cf)	5 bbls
7" J-55	20#	3020'	8 3/4"	surface; 485#x (1117 cf)	97 bbls
4 1/2" N-80 J-55	11.8# 10.5'	3020'	6 1/4"	TOC 2758'; 305#x (442 cf)	

29. LINER RECORD 5622'

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	5293'	

31. PERFORATION RECORD (Interval, size and number)

@1SPF
PLO 5634' - 5272' = 28 holes
UMF/CH 5214' - 4778' = 29 holes
Lewis 4292' - 4644' = 25 holes
Total Holes = 82

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

5272' - 5634'	10 bbls 15% HCL Acid, pumped 10290 gal 60Q
	Slickwater/Foam . Pumped 100000# 20/40 Brady Sand.
4778' - 5214'	10 bbls 15% HCL Acid, pumped 10290 gal 60Q
	Slickwater/foam pad, pumped 100000# 20/40 Brady Sand.
4292' - 4644'	10 bbls 15% HCL Acid, pumped 13440 gal 75Q N2 foam
	20# Linear Gel pad, pumped 170000# 20/40 Brady Sand

33. PRODUCTION
DATE FIRST PRODUCTION SI W/O FACILITIES
PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing
WELL STATUS (Producing or shut-in) SI

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO
5/3/07	1	1/2"			21 mcf	.25 bw	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)	
75#	SI - 300#		0	495 mcf	6 bw		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This will be a stand alone Mesa Verde Well.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Mary V. Minor TITLE Regulatory Technician DATE 5/11/07

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

MAY 15 2007

FARMINGTON FIELD OFFICE

NMOCD

Ojo Alamo	1994'	2141'	White, cr-gr ss.	Ojo Alamo	1994'
Kirtland	2141'	2903'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2141'
Fruitland	2903'	3173'	Dk gry-gr carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	2903'
Pictured Cliffs	3173'	3357'	Bn-Gry, fine grn, tight ss.	Pic. Cliffs	3173'
Lewis	3357'	3918'	Shale w/siltstone stringers	Lewis	3357'
Huerfanito Bentonite	3918'	4285'	White, waxy chalky bentonite	Huerfanito Bent.	3918'
Chacra	4285'	4762'	Gry fn grn silty, glauconitic sd stone w/drak gry shale	Chacra	4285'
Mesa Verde	4762'	5120'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	4762'
Menefee	5120'	5419'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5120'
Point Lookout	5419'		Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5419'



215412 JT

215412 JT

215412 JT