Submit 3 Copies To Appropriate District Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II		WELL API NO. 30-045-34240
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE FEE
District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		
	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		TSAH TAH RCUD MAY25'07
	Gas Well 🛛 Other	8. Well Number 36 #1 CONS. DIU.
2. Name of Operator		9. OGRID Number
ROSETTA RESOURCES		239235
3. Address of Operator C/O Walsh Engineering & Prod. Corp. 7415 East Main Street, Farmington, NM 87402		10. Pool name or <b>Wheter 3</b> Basin Fruitland Coal
4. Well Location	·	
Unit Letter G: 1550'	feet from the NORTH line and 1530' feet f	rom the EAST line
Section 36 Township	<u> </u>	ounty San Juan
。 第二章	11. Elevation (Show whether DR, RKB, RT, GR, etc.	
Pit or Below-grade Tank Application O	6753' GL	the Distriction and the office of the order of the heart
Pit type Depth to Groundwater	···	rom nearest surface water
·		
12. Check A	appropriate Box to Indicate Nature of Notice	, Report of Other Data
NOTICE OF IN	TENTION TO: SUI	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON   REMEDIAL WO	<del>_</del>
TEMPORARILY ABANDON	_	RILLING OPNS. P AND A
PULL OR ALTER CASING	MULTIPLE COMPL	NT JOB 🛛
OTHER: □	OTHER:	П
OTHER:   13. Describe proposed or comp	OTHER: leted operations. (Clearly state all pertinent details, a	nd give pertinent dates, including estimated date
13. Describe proposed or composed wo		
13. Describe proposed or comp	eted operations. (Clearly state all pertinent details, a	
<ol> <li>Describe proposed or composed of starting any proposed wo or recompletion.</li> </ol>	leted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A	attach wellbore diagram of proposed completion
13. Describe proposed or composed we of starting any proposed we or recompletion.  04/30/07 spud 8-3/4" surface h	leted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and
13. Describe proposed or composed of starting any proposed we or recompletion.  04/30/07 spud 8-3/4" surface he Set at 141'KB. Cemented with	rk). SEE RULE 1103. For Multiple Completions: A cole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub>	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and
13. Describe proposed or composed we of starting any proposed we or recompletion.  04/30/07 spud 8-3/4" surface h	rk). SEE RULE 1103. For Multiple Completions: A cole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub>	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and
<ul> <li>13. Describe proposed or composed we of starting any proposed we or recompletion.</li> <li>04/30/07 spud 8-3/4" surface he set at 141 KB. Cemented with 5 bbls of good cement to surface.</li> </ul>	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.	Attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and 1/4 #/sk celloflake. Circulated
<ul> <li>13. Describe proposed or composed we of starting any proposed we or recompletion.</li> <li>04/30/07 spud 8-3/4" surface he set at 141 KB. Cemented with 5 bbls of good cement to surface.</li> </ul>	rk). SEE RULE 1103. For Multiple Completions: A cole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub>	Attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and 1/4 #/sk celloflake. Circulated
13. Describe proposed or composed of starting any proposed we or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 141'KB.	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high).
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  Ind BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high). 0.5#, J-55, ST&C production casing.
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at Set casing at 1899'KB. Insert	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  Ind BOP. Pressure tested the BOP and casing the same statement of the same stateme	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high). 0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Typ	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  Ind BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high). 0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of good cement to good cement to surface of good cement to good cement to	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  Ind BOP. Pressure tested the BOP and casing the same statement of the same stateme	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high). 0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Typ (89 cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high). 0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Typ (89 cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high). 0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Typ (89 cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.  Report PT In proof	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the complex control of the control of	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx tement to surface. Released rig
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Typ (89 cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.  Pepper Proposed or composed or composed was on the surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/03/2007 TD 6-1/4" hole at 1500 sx (309cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.  Pepper Proposed or composed was or recompletion.	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the complete to the best of my knowledge above is true and complete to the best of my knowledge.	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx ement to surface. Released rig
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Type (89 cu. ft.) of Type 5, with 150 or 05/03/07.  Perpett PT The proof.  I hereby certify that the information a grade tank has been/will be constructed or	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the complex control of the control of	attach wellbore diagram of proposed completion 7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx ement to surface. Released rig
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Typ (89 cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.  Pepper Proposed or composed or composed was on the surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/03/2007 TD 6-1/4" hole at 1500 sx (309cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.  Pepper Proposed or composed was or recompletion.	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the complete to the best of my knowledge above is true and complete to the best of my knowledge.	attach wellbore diagram of proposed completion  7", 20#, J-55, ST&C new casing and and 1/4 #/sk celloflake. Circulated  g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx rement to surface. Released rig  ge and belief. I further certify that any pit or below-lor an (attached) alternative OCD-approved plan
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of the start of the surface of the su	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casing 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the strue and complete to the best of my knowled closed according to NMOCD guidelines \(\mathbb{A}\), a general permit \(\mathbb{L}\)	Attach wellbore diagram of proposed completion  7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated  g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436 KB. Cemented sk celloflake, followed by 75 sx tement to surface. Released rig  ge and belief. I further certify that any pit or beloward or an (attached) alternative OCD-approved plan  DATE 05/23/07
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of 5/01/07 NU the bradenhead at 05/03/2007 TD 6-1/4" hole at set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Type (89 cu. ft.) of Type 5, with 150 or 05/03/07.  Perpett PT The proof.  I hereby certify that the information a grade tank has been/will be constructed or	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl2 ce.  and BOP. Pressure tested the BOP and casing 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the closed according to NMOCD guidelines \(\omega\), a general permit \(\omega\)	attach wellbore diagram of proposed completion  7", 20#, J-55, ST&C new casing and and 1/4 #/sk celloflake. Circulated  g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx rement to surface. Released rig  ge and belief. I further certify that any pit or below-lor an (attached) alternative OCD-approved plan
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of the start of the surface of the set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Type (89 cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.  Perform for the information of the start of	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the colosed according to NMOCD guidelines , a general permit [Inc.	attach wellbore diagram of proposed completion  7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated  g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx seement to surface. Released rig  ge and belief. I further certify that any pit or belowdor an (attached) alternative OCD-approved plan  DATE 05/23/07  phone No. 505-327-4892
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of surface of good cement to surface of surface of surface of good cement to surface of surface of surface of good cement to surface of surf	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the colosed according to NMOCD guidelines , a general permit [Inc.	Attach wellbore diagram of proposed completion  7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated  g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436 KB. Cemented sk celloflake, followed by 75 sx tement to surface. Released rig  ge and belief. I further certify that any pit or beloward or an (attached) alternative OCD-approved plan  DATE 05/23/07
13. Describe proposed or composed was of starting any proposed was or recompletion.  04/30/07 spud 8-3/4" surface he set at 141'KB. Cemented with 5 bbls of good cement to surface of the start of the surface of the set casing at 1899'KB. Insert with 150 sx (309cu. ft.) of Type (89 cu. ft.) of Type 5, with 1/4 is at 1500hrs on 05/03/07.  Perform for the information of the start of	teted operations. (Clearly state all pertinent details, a rk). SEE RULE 1103. For Multiple Completions: A tole. Drilled to 145'. Ran 3 jts (135.60') of a 50 sx (59 cu. ft.) of Type 5 with 3% CaCl <sub>2</sub> ce.  and BOP. Pressure tested the BOP and casin 1935'KB. Ran 46 jts (1898.67') of 4-1/2", 1 float is at 1877'KB and the top of marker jo e 5, with 2% sodium metasillicate, and ½ #/#/sk celloflake. Circulated 18 bbls of good of the colosed according to NMOCD guidelines , a general permit [Inc.	attach wellbore diagram of proposed completion  7", 20#, J-55, ST&C new casing and and ½ #/sk celloflake. Circulated  g (250 psi-low and 1,000 psi-high).  0.5#, J-55, ST&C production casing. int is at 1436'KB. Cemented sk celloflake, followed by 75 sx seement to surface. Released rig  ge and belief. I further certify that any pit or belowdor an (attached) alternative OCD-approved plan  DATE 05/23/07  phone No. 505-327-4892