Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR

Form 3160-5 (February 2005)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT				FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007 5. Lease Serial No.		
				5. Lease Seria			
SUNDRY NOTICES AND REPORTS ON WELLS				NMSF-047039B			
Do not use t abandoned w	his form for proposals vell. Use Form 3160-3 (to drill or to re (APD) for such p	-enter an roposals.	6 / If Indian	Allotteeror Tribe Name		
SUBMIT IN TRIPLICATE- Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No.			
1. Type of Well Gas Well Other				8. Well Name and No.			
2. Name of Operator Robert L. B	ayless, Producer LLC			Bimson 9. API We	Federal #1G		
3a Address		3b. Phone No. (include area code)		03-045-33991			
P.O.Box 168 Farmington, NM 87499 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		(505)3262659		10. Field and Pool, or Exploratory Area Basin Fruitland Coal			
1400' FNL & 1425' FEL, See			11. County or Parish, State				
				San Ju	an, NM		
12. CHECK A	APPROPRIATE BOX(ES) TO	INDICATE NATU	IRE OF NOTICE,	REPORT, OF	OTHER DATA		
TYPE OF SUBMISSION		T	YPE OF ACTION	ACTION			
Notice of Intent	Acidize Alter Casing	Deepen		(Start/Resume)	Water Shut-Off		
Subsequent Report	Casing Repair	Fracture Treat New Construction	Reclamation Recomplete	_	Well Integrity ✓ Other Spud and Surface		
Final Abandonment Notice	Change Plans	Plug and Abandon			Casing		
	Convert to Injection	Plug Back	Water Dispo	osal			
determined that the site is read 5/26/07 Move in and rig up D&I hole for casing. Rig up to ft. Rig up Halliburton V 1/8#/sx Polyflake mixed :	o drilling Services. Spudded W o run casing. Run 3 joints of 7" Vell Services and cement casing	ell at 10:00 am 05/26, 20 # J-55 STC surfa g to Surface with 66 s	2007. Drilled 8 3/4; ce casing, 3 central x (77 cubic ft) Clas	surface hole to 14 izers and a guide s G Premium Ce	•		
casing to 250/750 psi, hel	and make up wellhead. Nipple i ld OK Make up 6 1/4" BHA. ft. Took surveys at 130 ft (1/2 d	Frip in the hole and t	ag top of cement at	surface casing. F 95 ft. Drilled ou	Pressure test BOP and surface to teement shoe to 145 ft and RCVD JUN5'07 OIL CONS. DIV. DIST. 3		
14. I hereby certify that the for Name (Printed/Typed)	regoing is true and correct						
Habib J. Guero	rero	Title	Engineer				
Signature Volume		Date	Date		05/29/2007		
	THIS SPACE FOR	FEDERAL OR	STATE OFFI	CE USE			
Approved by			Title		Date		
Conditions of approval, if any, ar certify that the applicant holds le which would entitle the applicant		Office					
		a crime for any person	knowingly and willi	fully to make to an	y department or agency of the United		

(Instructions on page 2)

NMOCD

المراجعة المكالك والمراط