This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

Hour, Date, Shut-In

Lower

Completion

## NEW MEXICO OIL CONSERVATION DIVISION

Page 1

outheast New Me	exico	NORTHWES	T NEW ME	EXICO F	PACKER	LEA]	KAGE TI	EST	Rev	ised June 10, 2003
Operator		DEVON ENERG	Y		_ Lease N	lame	N	EBU	Well No. 333	
Location Of	Well: Unit Letter	Sec	19	Twp	31-N	_Rge	6-W	_API # 30-0		
	Name	of Reservoir or Po	ol	1	Type of Prod	l.	Method	l of Prod.	Prod.	. Medium
	1				(Oil or Gas)		(Flow or	r Art. Lift)	(Tbg. Or Csg.)	
Upper Completion	PIC			GAS		FLOW		CASING		
Lower Completion			GAS			FLOW		TUBING		
		1	Pre-Flow Sh	ut-In Pre	essure Data	<b>a</b>				
Upper	Hour, Date, Shut-In		Length of Ti				bilized? (Yes	or No)		
Completion		600hrs 05-24-07 306hrs			570psi		YES			
Lower	Hour, Date,Shut-In		Length of Ti	me Shut-I	t-In SI				bilized? (Yes or No)	
Completion	1600hrs 0	-		168hrs		1241psi			YES	
Time Hour, Date)	t (hour, date)* 1600hrs 06-04-07 Zo  Lasped Time Pressure  Since* Upper Compl. Lower Compl			Prod. Zone Ro		Remarks		Lower (D)	,	
1600hrs 06- 04-07	24hsr	570psi	Lower Compt.		1em	<b>р.</b>	1100mef/d Flow Rate			
1000hrs 06- 05-07	24hrs	570psi	98 <sub>p</sub>	si	Lower comp. flow rate 5		low rate 555 i	mef/d		
10:00 hrs 6-5	24hrs	570 psi	10% differential				550me	:f/d turned on	prod of upper	prod (MV)
										RCVD JUN
										OIL CONS
										DIST.
Production F	Late During Test	J.			ı		1			D2011
Oil:	BOPD b	BOPD based on Bbls. In		Hrs.		- Grav.		GOR _		
Sas:	MCFPD; Test thru (Orifice or Meter):				Meter					
			Mid-Test Sh	ut-In Pre	essure Data	9.				
Upper	Hour, Date, Shut-In		Length of Ti	Length of Time Shut-In			SI Press. P	sig	Stabilized? (	(Yes or NO)
Completion										

(Continue on reverse side)

Length of Time Shut-In

Stabilized? (Yes or NO)

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Flow Test No. 2

Commenced	at (hour, date)*		Zone Pro	One Producing (Upper or Lower):						
Time	Lasped Time	Pre	ssure	Prod. Zone	Remarks					
(Hour, Date)	Since*	Upper Compl.	Lower Compl.	Temp.						
					<u> </u>					
					ļ					
Production F	Rate During Test				.,,					
Oil:	BOPD based on		Bbls. In	Hrs.	Grav.	GOR				
Gas:	MCFPD; Test thru (Orifice or Meter):									
Remarks:										
I hereby cert	ify that the information	herein contained is t	rue and complete to	the best of my kno	wledge.					
	II IAC 4	0 2007								
Appoved		L 2 2007		o <sub>F</sub>	perator	DEVON ENERGY				
New Mexico	Oil Conservation Division									
Ву	HVill	anveva	· ·	Title	Lease Operator	• 2				
•	Damiel O			-		,				
Title	Debuty Of	l & Gas Ins	spector,	- E-mail	Address <u>tyler</u>	tyler.phillips@dvn.com				
	District #3				2/15/	July June 5, 2007				

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. I, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).