

(Other instructions on
reverse side)

Expires: February 28, 1995

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1 a. TYPE OF WELL:

OIL
WELL ☐GAS
WELL ☒DRY ☐

OTHER

b. TYPE OF COMPLETION:

NEW
Well ☒WORK
OVER ☐DEEP-
EN ☐PLUG
BACK ☐DIFF.
CENTR. ☐

OTHER

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325 - 1821

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface 1450' FNL & 660' FEL (SE/4 NE/4)

At top prod. interval reported below

same

At total depth

same

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR PARISH

San Juan

13. STATE

NM

15. DATE SPUDDED

8/15/2006

16. DATE T.D. REACHED

8/18/2006

17. DATE COMPL.

(Ready to prod.)

5/31/2007

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6632' GL

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

1360'

21. PLUG BACK T.D., MD & TVD

1304'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

TD

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*

1133'-1153' (Fruitland Coal)

25. WAS DIRECTIONAL SURVEY MADE

no

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR-CNL-CCL

27. WAS WELL CORED

no

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8-5/8" J-55	24#	126'	12-1/4"	90 sx Type 5 cement w/2% CaCl ₂ w/1/4# celloflake/sx. Circ 4 bbls cement	
5-1/2" J-55	15.5#	1344'	7"	85 sx Type 5 cement w/3#/sx PhenoSeal & 1/4# celloflake/sx. Tail w/50 sx	
				Type 5 cement w/3# PhenoSeal & 1/4# celloflake/sx. Circ 8 bbls cement	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	1226'	N/A

31. PERFORATION RECORD (Interval, size and number)

1133'-1153' w/4 spf (total 80 holes)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)

1133'-1153'

AMOUNT AND KIND OF MATERIAL USED

500 gals 15% HCL; 80,000# 20/40 Brady sand;
42,575 gals AquaSafe gel

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump)					WELL STATUS (Producing or shut in)	
N/A							Shut in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL - BBL.	GAS - MCF.	WATER - BBL.	GAS - OIL RATIO	
			→				RCVD JUN11'07	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24 - HOUR RATE	OIL - BBL.	GAS - MCF.	WATER - BBL.	OIL GRAVITY - API (CORR.)	OIL CONS. DIV. DIST. 3	
		→						

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)


Vented - to be sold - A sundry notice of well test will be submitted in future

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing information is complete and correct as determined from all available records

SIGNED


John Alexander

Title

Vice-President

Date

6/4/2007

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

B 6/4

FARMINGTON FIELD OFFICE

JUN 08 2007

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof: cored intervals; and all drill-stem, tests, including depth interval tested on used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS DEPTH	TRUE VERT DEPTH
				Ojo Alamo Kirtland Fruitland Pictured Cliffs Total Depth	284' 382' 661' 1157' 1360'	