

submitted in lieu of Form 3160-5
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2007 JUN 11 PM 3:32

1. Type of Well
GAS

5. Lease Number
NMSF-078198
6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP

8. Well Name & Number

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

9. NYE SRC 15N
API Well No.

30-045-34143

4. Location of Well, Footage, Sec., T, R, M
Sec., T--N, R--W, NMPM

10. Field and Pool

Basin Dakota/Blanco MV

Unit B (NWNE) 660' FNL & 1885' FEL, Sec. 25, T30N, R11W NMPM

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Log & Squeeze

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Plugging

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Final Abandonment

☐ Altering Casing

☐ Conversion to Injection

RCVD JUN14'07
OIL CONS. DIV.
DIST. 3

13. Describe Proposed or Completed Operations

3/17/07 MIRU Bluejet wireline. Run gauge ring to 7178'. POOH LD Tool. Run GR/CCL/CBL from PBTD 7179' log tag to surface. TOC @ 4510'. Marker joints: Top @ 3236' - 3245'. Bottom @ 6763' - 6773'. 7" @ 4502'. MIRU GSL run log from PBTD @ 7179' to 4200', 200' above TOC. RD Release Bluejet.

3/27/07 RU rig & equip. ND Frac valve. NU BOP. RU rig floor. MU 3 3/4" mill & bit sub. Cont in hole w/mill, tag 4' cement above FC. MO 4' cement, tag float collar @ 7178'. MO collar & 4 1/2" shoe.

3/30/07 We drilled out below the 4 1/2" shoe - 7411' to 7458' and got wet at the top of Burro Canyon. Requesting to set retainer @ 7170' @ the joint above the collar & squeeze with either Type III or Class G cement with an excess of 100%. Plug will be set between 7258' - shoe @ 7170'. Verbal approval from Troy Salyers (BLM) to continue.

4/2/07 Cement retainer set @ 7170'. RU to Cement. Pumped 25 sx(29cf-5 bbls) Type III Class G w/Halad 9, 1% CFR3, 1% HR-5. Cement plug set @ 7258'. Squeezed Burro Canyon formation, final pressure @ 855#. RD cement.

PT 4 1/2" casing to 4100# 15/min - good test.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 6/11/07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD
JUN 12 2007
FARMINGTON FIELD OFFICE
T. Salyers