

4029

Exhibit D

DATA SHEET FOR DEEP GROUND-BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

30-039-24717

Operator MERIDIAN OIL CO. Location: Unit NE Sec. 9 Twp 30 Rng 6

Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6 # 403

cps 2167w

Elevation 6217 Completion Date 11/13/90 Total Depth 420 Land Type N/A

Casing Strings, Sizes, Types & Depths 20 ft. 8" PVC Casing

If Casing Strings are cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Bentonite Plugs set 375 to 420 ft.

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. Wet at 140 ft., Water at 240 ft. got a sample

Depths gas encountered: 400 to 420 ft.

Ground bed depth with type & amount of coke breeze used: 10,000 lbs of Ashbury Petroleum Coke used 375 ft.

Depths anodes placed: 355, 220, 170, 164, 157, 150, 120, 112, 105, 95

Depths vent pipes placed: 400 ft. 1" PVC

Vent pipe perforations: 280 ft. perforated

Remarks: gb #1

RECEIVED
MAY 31 1991
OIL CON. DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.