

602

30-045-05691

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc Location: Unit H Sec 27 Twp 26 Rng 9Name of Well/Wells or Pipeline Serviced Huerfano #55

2223W

Elevation 6208 Completion Date 11-11-91 Total Depth 316 Land Type FCasing Strings, Sizes, Types & Depths Set 100' of P.O.C. casing with 22 sacks of neat cement.If Casing Strings are cemented, show amounts & types used 22 sacksIf Cement or Bentonite Plugs have been placed, show depths & amounts used
no plugsDepths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. H₂O is at 130' and is clearDepths gas encountered: no gasGround bed depth with type & amount of coke breeze used: 316' with 43 sacks of Asbury 4518Depths anodes placed: #1 is at 285' #12 is at 175'Depths vent pipes placed: 316' - surfaceVent pipe perforations: up to 150'

Remarks:

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2223-W	P/L NAME(*), NUMBER(*) Huertano #55					
Q # m886	TOTAL	VOLTS 11.72	AMPS 30.9	- OHMS .38	DATE 11-11-91	NAME
REMARKS (notes for construction log) H ₂ O is at 130', vent pipe is perforated up to 150'						

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
100			295	1.6		490			685			
105			300	1.0		495			690			
110			305	1.9		500			695			
115			310	1.7		505			700			
120			315	TD316		510			ANODE	DEPTH	NO	FULLY
125			320			515			*		COKE	COKE'D
130			325			520			1	285	3.1	2.0
135			330			525			2	275	3.4	2.8
140	2.0		335			530			3	265	3.2	2.7
145	1.7		340			535			4	255	3.0	2.1
150	1.9		345			540			5	245	3.0	2.4
155	2.5		350			545			6	235	3.0	2.6
160	2.3		355			550			7	225	2.8	2.4
165	2.2		360			555			8	215	3.1	2.9
170	2.0		365			560			9	205	2.7	2.6
175	2.1		370			565			10	195	2.7	2.4
180	2.2		375			570			11	185	2.7	2.9
185	2.2		380			575			12	175	2.4	2.8
190	2.3		385			580			13			
195	2.3		390			585			14			
200	2.1		395			590			15			
205	2.4		400			595			16			
210	2.5		405			600			17			
215	2.3		410			605			18			
220	2.3		415			610			19			
225	2.5		420			615			20			
230	2.5		425			620			21			
235	2.6		430			625			22			
240	2.4		435			630			23			
245	2.4		440			635			24			
250	2.7		445			640			25			
255	2.7		450			645			26			
260	2.8		455			650			27			
265	2.8		460			655			28			
270	3.0		465			660			29			
275	3.1		470			665			30			
280	2.8		475			670						
285	2.9		480			675						
290	2.3		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist