

604 709-30-045-27235
1- 30-045-07107
5- 30-045-20865
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO 22250

Operator Meridian Oil Location: Unit N Sec. 26 Twp 28 Rng 9

Name of Well/Wells or Pipeline Served LACKEY # 709 # 1
+ # 5

Elevation _____ Completion Date 12-3-91 Total Depth 382' Land Type F

Casing Strings, Sizes, Types & Depths 8" PVC surface
CASING - 95' DEEP

If Casing Strings are cemented, show amounts & types used YES; with
23 SACKS NEAT CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used
YES - 105' TO 90'

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 110'

Depths gas encountered: 380'

Ground bed depth with type & amount of coke breeze used: 382' DEEP
with 5,250 lbs Asbury 4518 Flo COKE & LORESCO Type S L

Depths anodes placed: 354, 345, 335, 325, 300, 290, 280, 270, 205, 195, 185
160

Depths vent pipes placed: 382'

Vent pipe perforations: bottom 250'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2225-W		P/L NAME(s), NUMBER(s) LACKEY H#709 #1 #5									
WO # 1013	TOTAL	VOLTS 11.56	AMPS 31.4	- OHMS .368	DATE 12-3-91	NAME MRW					
REMARKS (notes for construction log) 95' CASING 23 SACKS CEMENT											
N 26-28-9 Drilled 400' LOGGED 382 H ₂ O AT 100'											
Perforated bottom 250' MAKING SMALL AMOUNT OF GAS; Installed											
5 BAGS LORESCO 100 Ashury 4518 FLO CURE Plug											

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100	1.9		295	3.5		490			685			
105	1.9		300	3.4		495			690			
110	2.8		305	2.3		500			695			
115	3.8		310	1.9		505			700			
120	4.0		315	2.4		510			ANODE	DEPTH	NO	FULLY
125	4.2		320	2.8		515			*		COKE	COKE D
130	3.7		325	3.2		520			1	354	2.8	6.7
135	3.5		330	3.5		525			2	345	3.5	7.4
140	3.3		335	3.6		530			3	335	3.6	7.3
145	3.2		340	3.5		535			4	325	3.2	6.6
150	2.9		345	3.5		540			5	300	3.6	6.8
155	3.1		350	3.3		545			6	290	4.1	7.5
160	3.1		355	2.8		550			7	280	4.1	7.6
165	2.8		360	2.6		555			8	270	4.1	7.7
170	2.6		365	2.6		560			9	205	3.1	6.9
175	2.6		370	2.3		565			10	195	3.3	7.4
180	3.0		375	2.0		570			11	185	3.7	7.9
185	3.6		380	TD	382	575			12	160	3.1	6.9
190	3.3		385			580			13			
195	3.3		390			585			14			
200	3.1		395			590			15			
205	3.1		400			595			16			
210	2.7		405			600			17			
215	2.5		410			605			18			
220	2.7		415			610			19			
225	2.7		420			615			20			
230	2.8		425			620			21			
235	2.6		430			625			22			
240	2.5		435			630			23			
245	2.9		440			635			24			
250	2.9		445			640			25			
255	2.8		450			645			26			
260	2.3		455			650			27			
265	3.4		460			655			28			
270	3.9		465			660			29			
275	4.2		470			665			30			
280	4.0		475			670						
285	4.3		480			675						
290	3.6		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist