

597

301 30-045-27967

56 30-045-11497

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

281910

Operator Meredian Oil Inc. Location: Unit N Sec. 12 Twp 32 Rng 10Name of Well/Wells or Pipeline Served S.T. 32-9 #301 andS.T. 32-9 #56Elevation 6453 Completion Date 7-17-91 Total Depth 390 Land Type FCasing Strings, Sizes, Types & Depths Set 100' of 8" P.O.C.If Casing Strings are cemented, show amounts & types used 21 sacks
of neat cementIf Cement or Bentonite Plugs have been placed, show depths & amounts used
noneDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. From 120' to 130' with clear.Depths gas encountered: no gasGround bed depth with type & amount of coke breeze used: 390' with
Asbury 4518Depths anodes placed: #1 at 355 and #15 at 170'Depths vent pipes placed: 320'Vent pipe perforations: perforated up to 100'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.]

If any of the above data is unavailable, please indicate so. Copies of all
logs, including Drillers Log, Water Analyses & Well Bore Schematics should
be submitted when available. Unplugged abandoned wells are to be included.Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2549-2	D/L NAME(s), NUMBER(s) S-J-32-9-4301 # 56					
WD # 1299	TOTAL 12.28	VOLTS 12.28	AMPS 2.57	- OHMS .48	DATE 7-17-91	NAME P. Smith

REMARKS (notes for construction log):
 water is at 140' and
 vent pipe is perforated up to 100'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100	.8		295	.8		490			685			
105	.8		300	.6		495			690			
110	1.0		305	1.2		500			695			
115	1.0		310	4.0		505			700			
120	1.0		315	4.2	(2)	510			ANODE	DEPTH	NO.	FULLY
125	.8		320	5.7		515			*		COKE	COKE'D
130	1.0		325	1.5		520			1	35.5	3.0	5.1
135	2.9		330	1.3		525			2	31.5	4.2	6.3
140	3.8		335	2.2		530			3	27.0	3.3	5.0
145	3.8		340	2.2		535			4	25.0	3.1	5.2
150	3.4		345	2.2		540			5	24.0	3.1	5.5
155	3.1		350	3.2		545			6	23.0	2.8	5.0
160	2.4		355	3.0	(1)	550			7	22.0	3.1	5.4
165	3.1		360	2.2		555			8	21.0	3.7	6.8
170	3.7	(12)	365	2.5		560			9	20.0	2.8	6.7
175	4.0		370	2.0		565			10	19.0	3.8	7.8
180	4.0	(11)	375	1.2		570			11	18.0	4.1	8.3
185	4.0		380	.8		575			12	17.0	3.7	7.9
190	3.4	(10)	385	.8		580			13			
195	2.9		390	TD		585			14			
200	2.5	(9)	395			590			15			
205	3.4		400			595			16			
210	3.6	(8)	405			600			17			
215	3.3		410			605			18			
220	2.8	(7)	415			610			19			
225	2.6		420			615			20			
230	2.8	(6)	425			620			21			
235	3.1		430			625			22			
240	3.5	(5)	435			630			23			
245	3.1		440			635			24			
250	2.5	(4)	445			640			25			
255	2.2		450			645			26			
260	2.2		455			650			27			
265	3.1		460			655			28			
270	3.1	(3)	465			660			29			
275	2.2		470			665			30			
280	1.5		475			670						
285	1.1		480			675						
290	.9		485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist