

273-30045-28033

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

591

59-30-045-11338

2211W

Operator Meridian Oil Inc. Location: Unit L Sec. 19 Twp 30 Rng 9

Name of Well/Wells or Pipeline Served San Juan 32-9#273
and San Juan 32-9#59

Elevation _____ Completion Date 7-20-91 Total Depth 340 Land Type F

Casing Strings, Sizes, Types & Depths Set 100' of 8" P.V.C.

If Casing Strings are cemented, show amounts & types used Used 22
sacks of neat cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Water is at 150' and clear

Depths gas encountered: no gas

Ground bed depth with type & amount of coke breeze used: 340' with
46 sacks of Loresea SW

Depths anodes placed: #1 is at 305' and #12 is at 165'

Depths vent pipes placed: 300'

Vent pipe perforations: up to 120'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2211-0	P/L NAME(s), NUMBER(s) S.J. 32-9 #273, #59					
WG # 2119	TOTAL	VOLTS 12.17	AMPS 18.9	- OHMS 64	DATE 7-20-91	NAME R Smith

REMARKS (notes for construction log)

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100			295	1.7	⑤	490			685			
105			300	1.9		495			690			
110			305	1.7	①	500			695			
115			310	1.0		505			700			
120			315	.8		510			ANODE	DEPTH	NO.	FULLY
125			320	.8		515			*	COKE	CON'D	
130	.7		325	.9		520			1	305	2.1	3.3
135	1.1		330	1.3		525			2	295	1.8	3.7
140	1.7		335	1.3		530			3	270	2.7	4.6
145	1.6		340	TD		535			4	260	3.0	5.1
150	1.3		345			540			5	250	2.6	5.0
155	1.9		350			545			6	240	1.8	4.8
160	3.1		355			550			7	230	2.5	5.4
65	3.0	⑫	360			555			8	220	3.1	5.8
70	2.9		365			560			9	210	2.5	5.2
175	3.1	⑩	370			565			10	285	2.2	5.1
180	2.6		375			570			11	175	3.2	5.9
185	2.1	⑩	380			575			12	165	3.2	5.7
190	1.7		385			580			13			
195	1.4		390			585			14			
200	1.5		395			590			15			
205	1.5		400			595			16			
210	2.6	⑨	405			600			17			
215	2.9		410			605			18			
220	3.0	⑧	415			610			19			
225	5.8		420			615			20			
230	2.4	⑦	425			620			21			
235	1.9		430			625			22			
240	1.7	⑬	435			630			23			
245	2.6		440			635			24			
250	2.5	⑤	445			640			25			
255	2.8		450			645			26			
260	2.8		455			650			27			
265	2.4	③	460			655			28			
270	1.8		465			660			29			
275	.9		470			665			30			
280	1.0		475			670						
285	1.0		480			675						
70	1.2		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist