

3 = 30-039-06794

DATE: 4-25-96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit M Sec 35 Twp 27 Rng 3

Name of Well/Wells or Pipeline Serviced Sicavilla 95#3

Elevation _____ Completion Date 4-25-96 Total Depth 380' Land Type I

Casing Strings, Sizes, Types & Depths 60' 8" PUC Casing

If Casing Strings are cemented, show amounts & types used yes
13 sacks

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 190' - Fresh

RECEIVED
FEB 1 9 1997

Depths gas encountered: None OIL CON. DIV.

Ground bed depth with type & amount of coke breeze used: 380'
4250 lbs Asbury

Depths anodes placed 340, 353, 345, 337, 329, 321, 300, 293, 285, 265, 258, 251, 244, 237, 180

Depths vent pipes placed: Sur Face to 380'

Vent pipe perforations: From 130' to 380'

Remarks: No gas encountered during drilling of hole

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME (S), NUMBER (S)					DATE	NAME
2965-11	Sicarilla 95 ^{#3}					4-25-96	David Ashworth
WD #	TOTAL	VOLTS	AMPS	- OHMS			
2211		12.2	30.1	140			

REMARKS (NOTES FOR CONSTRUCTION LOG)

85 bags 4250/lbs 40'-190' Remote As 500'E = 71P
 60'-132ggs Perf 250'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	2.8		490			685			
105			300	2.7	7	495			690			
110			305	1.8		500			695			
115			310	1.1	6	505			700			
120			315	1.8		510			ANODE	DEPTH	NO	FULLY
125			320	2.8	5	515			*		COKE	COKE
130			325	2.7		520			1	360	2.7	6.1
135			330	2.7	4	525			2	353	2.8	6.8
140			335	2.7		530			3	345	2.7	6.8
145			340	2.8	3	535			4	337	2.7	7.1
150			345	2.6		540			5	329	2.8	7.4
155			350	2.8	2	545			6	321	2.9	7.6
160			355	2.7		550			7	300	3.0	8.1
165			360	2.7	1	555			8	293	2.7	7.7
170	1.3		365	1.6		560			9	285	2.7	7.8
175	1.4		370	1.1		565			10	265	2.0	7.4
180	2.3		375	1.1		570			11	258	2.0	7.5
185	1.8		380	380TD		575			12	251	2.7	7.8
190	1.4		385			580			13	244	2.6	7.8
195	1.4		390			585			14	237	2.6	7.6
200	1.3		395			590			15	180	2.2	7.4
205	1.2		400			595			16			
210	1.0		405			600			17			
215	1.5		410			605			18			
220	1.4		415			610			19			
225	1.1		420			615			20			
230	1.0		425			620			21			
235	1.5	13	430			625			22			
240	2.6		435			630			23			
245	2.6	12	440			635			24			
250	2.6		445			640			25			
255	2.5	11	450			645			26			
260	2.7		455			650			27			
265	2.0	10	460			655			28			
270	1.2		465			660			29			
275	1.1		470			665			30			
280	2.1	9	475			670						
285	2.7		480			675						
290	2.6	8	485			680						

DISTRIBUTION - ORIGINAL - permanent CPS FILE

COPY

- Division Corrosion Supervisor

COPY

- Region Corrosion Specialist