

#44 = 30-039-07630

3/18/96

3420

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit A Sec. 17 Twp 29 Rng 07

Name of Well/Wells. or Pipeline Serviced _____

SAN JUAN 29-7 #44

Elevation 6666 Completion Date 3/18/96 Total Depth 485' Land Type F

Casing Strings, Sizes, Types & Depths 3 1/2 SET 99' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used CEMENTED
WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT A FRESH WATER SEEP AT 220'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 485' DEPTH.
USED 64 SACKS OF LORESCO SW (6400#)

Depths anodes placed: 445', 420', 395', 385', 365', 355', 345', 330', 320', 310', 290', 270', 255', 235', + 215'.

Depths vent pipes placed: SURFACE TO 485'.

Vent pipe perforations: BOTTOM 360'.

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 0087-W P/L NAME(S), NUMBER(S) S.J. 29-7 #44
 NO 2406 TOTAL VOLTS 11.23 AMPS 24.2 OHMS .464 DATE 3/18/96 NAME JOHN L. MOSS

REMARKS (notes for construction log) Driller Reported A Water Seep
 AT 220'. INSTALLED 485' OF 1" PE VENT PIPE, WITH THE
 BOTTOM 360' PERFORATED. COKE BREEZE TO 115'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE			ANODE			ANODE			ANODE		
100	↑		295	1.8		490			685			
105			300	1.8		495			690			
110			305	2.0		500			695			
115			310	2.2	-10	505			700			
120			315	2.2		510			ANODE	DEPTH	NO	FULL
125			320	2.7	-9	515					COKE	COKE
130			325	2.4		520			1	445'	1.9	4.0
135	SANDSTONE		330	2.3	-8	525			2	420'	2.6	5.3
140			335	2.1		530			3	395'	2.2	5.3
145			340	2.1		535			4	385'	2.1	5.2
150			345	2.3	7	540			5	365'	2.6	5.7
155			350	2.1		545			6	355'	2.5	5.6
160			355	2.5	-6	550			7	345'	2.2	5.0
165			360	2.3		555			8	330'	2.5	5.5
170			365	2.5	-5	560			9	320'	2.6	5.5
175			370	2.0		565			10	310'	2.2	5.1
180			375	2.0		570			11	290'	2.3	5.1
185	↓		380	2.1		575			12	270'	2.2	4.9
190	.3		385	2.1	4	580			13	255'	2.0	4.6
195	.4		390	2.2		585			14	235'	2.3	4.6
200	.7		395	2.1	3	590			15	215'	2.5	5.0
205	.7		400	2.0		595			16			
210	.9		405	1.7		600			17			
215	2.3	-15	410	1.8		605			18			
220	2.8		415	1.7		610			19			
225	2.1		420	2.5	2	615			20			
230	1.8		425	1.7		620			21			
235	2.4	-14	430	1.9		625			22			
240	2.2		435	1.7		630			23			
245	1.7		440	1.8		635			24			
250	1.9		445	1.9	1	640			25			
255	2.1	-13	450	1.4		645			26			
260	2.0		455	.5		650			27			
265	2.0		460	.4		655			28			
270	2.1	-12	465	.4		660			29			
275	1.8		470	.3		665			30			
280	1.7		475	.2		670						
285	2.2		480	.2		675						
290	2.3	-11	485	T.D. 485'		680						

DISTRIBUTION - ORIGINAL - REPRESENTS CPS FILE
 CEEV - Division Correction Supervisor
 CEEV - Region Correction Specialist