

#3A = 30-039-21166

DATE: 4-23-96DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Location: Unit D Sec. 35 Twp 27 Rng 3Name of Well/Wells or Pipeline Serviced Jicarilla 95 #3AElevation _____ Completion Date 4/23/96 Total Depth 435' Land Type ICasing Strings, Sizes, Types & Depths 60' 8" PVC casingIf Casing Strings are cemented, show amounts & types used Cemented
with 10 bagsIf Cement or Bentonite Plugs have been placed, show depths & amounts used
NoneDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 150' - FreshRECEIVED
FEB 19 1997Depths gas encountered: None OIL CON. DIV.Ground bed depth with type & amount of coke breeze used: 435'5300 lbs AsburyDepths anodes placed: 410', 400', 390', 380', 370', 360', 350', 340', 300', 275', 265', 258', 220', 210', 200'Depths vent pipes placed: Surface to 435'Vent pipe perforations: From 170' to 435'Remarks: No gas encountered during drilling of hole

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME (S), NUMBER (S)				
2946-W	Sicari/la 95 #3A				
NO	TOTAL VOLTS	AMPS	OHMS	DATE	NAME
2F73	12.9	34.1	38	4-23-96	David Ashworth
REMARKS (NOTES FOR CONSTRUCTION LOG)					

Drilled 440' 60'-10 Bags Ref 265
 435TD 106 Bags 5300 lbs Ash H₂O-150

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	"		ANODE	"		ANODE	"		ANODE	"	
100			295	1.5		490			685			
105			300	3.1	9	495			690			
110			305	2.4		500			695			
115			310	1.2		505			700			
120			315	1.3		510			ANODE	DEPTH	NO	FULL
125			320	1.5		515			"		COKE	COKE
130			325	1.7		520			1	410	2.5	6.9
135			330	2.0		525			2	400	2.6	7.2
140			335	2.8		530			3	390	2.8	7.9
145			340	2.5	8	535			4	380	2.6	7.8
150	2.7		345	2.4		540			5	370	2.7	8.0
155	2.7		350	2.7	7	545			6	360	2.8	8.4
160	2.5		355	2.7		550			7	350	2.7	8.1
165	2.2		360	2.4	6	555			8	340	2.7	8.1
170	2.7		365	2.8		560			9	300	2.7	8.6
175	2.7		370	2.8	5	565			10	275	2.7	8.3
180	1.6		375	2.6		570			11	265	3.0	9.0
185	1.3		380	2.6	4	575			12	258	2.6	8.7
190	1.3		385	2.6		580			13	220	2.7	8.8
195	1.4		390	2.8	3	585			14	210	2.6	8.5
200	2.7	15	395	2.7		590			15	200	2.9	8.8
205	2.8		400	2.6	2	595			16			
210	2.5	14	405	2.3		600			17			
215	2.4		410	2.6	1	605			18			
220	2.5	13	415	2.5		610			19			
225	1.1		420	2.6		615			20			
230	.7		425	2.3		620			21			
235	.7		430	435TD		625			22			
240	.6		435			630			23			
245	1.0		440			635			24			
250	1.6		445			640			25			
255	1.9	12	450			645			26			
260	2.4		455			650			27			
265	2.7	11	460			655			28			
270	2.6		465			660			29			
275	2.2	10	470			665			30			
280	1.8		475			670						
285	1.4		480			675						
290	1.2		485			680						

DISTRIBUTION - ORIGINAL - PERMANENT CPS FILE

CCBY - Division Correction Supervisor
 CCBY - Region Correction Specialist