

#48A = 30-039-21626

#141 = 30-039-24145

3421

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

CP1944W

Operator Meridian Oil Inc. Location: Unit P Sec. 8 Twp 29 Rng 07

Name of Well/Wells. or Pipeline Served _____

SAN JUAN 29-7 #48A AND #141

Elevation 6763 Completion Date 3/14/96 Total Depth 483' Land Type F

Casing Strings, Sizes, Types & Depths 3 1/2 SET 100' OF 8" PVC CASING

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used CEMENTED

WITH 23 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 240', AND MORE

AT 310'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 483' DEPTH.

USED 64 SACKS OF LORESCO SW (6400#)

Depths anodes placed: 460', 445', 425', 415', 405', 380', 360', 345', 335', 324', 315', 305', 295', 150', + 140'

Depths vent pipes placed: SURFACE TO 483'.

Vent pipe perforations: BOTTOM 360'.

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CP1944u

CP# 1944-10 P/L NAME(S), NUMBER(S) S.J. 29-7 #141 AND #48A
 -O -2E02 TOTAL VOLTS 11.53 AMPS 24.7 - OHMS .467 DATE 3/14/96 NAME JOHN L. MOSS
 2E03

REMARKS (NEED FOR CONSTRUCTION LOG)

Driller Reported some water

AT 240' AND MORE AT 310'. INSTALLED 483' OF 1" PE VENT
 PIPE, WITH THE BOTTOM 360' PERFORATED. CORE
 Breeze To 115.

DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE
100	.7		295	2.2	13	490			685		
105	1.2		300	2.4		495			690		
110	.9		305	2.2	12	500			695		
115	1.4		310	2.3		505			700		
120	1.2		315	2.4	11	510					
125	1.6		320	2.4		515					
130	2.1		325	1.9	10	520					
135	2.6		330	2.4		525			1	460	2.5
140	2.3	15	335	2.3	9	530			2	445	2.5
145	2.1		340	2.0		535			3	425	2.1
150	2.9	14	345	2.0	8	540			4	415	2.5
155	2.4		350	1.9		545			5	405	2.3
160	1.0		355	1.8		550			6	380	2.2
165	.7		360	2.2	7	555			7	360	2.2
170	.7		365	1.9		560			8	345	2.0
175	.7		370	1.9		565			9	335	2.3
180	.6		375	2.0		570			10	324	2.2
185	.4		380	2.2	6	575			11	315	2.3
190	.4		385	1.9		580			12	305	2.1
195	.5		390	1.8		585			13	295	2.2
200	.5		395	1.7		590			14	150	2.9
205	.5		400	1.9		595			15	140	2.3
210	.6		405	2.7	5	600			16		
215	.7		410	2.6		605			17		
220	.8		415	2.4	4	610			18		
225	.9		420	2.2		615			19		
230	.7		425	2.0	3	620			20		
235	1.1		430	1.8		625			21		
240	1.8		435	1.6		630			22		
245	1.5		440	1.7		635			23		
250	1.2		445	2.4	2	640			24		
255	.6		450	2.0		645			25		
260	.6		455	2.3		650			26		
265	.6		460	2.6	1	655			27		
270	.6		465	2.2		660			28		
275	.8		470	2.4		665			29		
280	1.5		475	2.2	483	670			30		
285	1.4		480			675					
290	1.7		485			680					

DISTRIBUTION - ORIGINAL - DEPARTMENT CPS FILE

COPY

- Division Correction Subdivision