

#330= 30-039-25522

#53= 30-039-07158

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit M Sec. 05 Twp 27 Rng 05

Name of Well/Wells or Pipeline Serviced _____

S. J. 27-5 #330 AND #53

Elevation _____ Completion Date 12/2/95 Total Depth 412' Land Type P

Casing Strings, Sizes, Types & Depths 12 1/2 SET 100' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT FRESH WATER AT 220'

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 412' DEPTH.

USED 102 SACKS OF ASBURY 218R (5100#)

Depths anodes placed: 375', 365', 355', 345', 335', 325', 315', 307', 250', 240', 230', 180', 160', 150', + 140'

Depths vent pipes placed: SURFACE TO 412'

Vent pipe perforations: BOTTOM 280'

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2848-W P/L NAME(S), NUMBER(S) S.J. 27-5 #330 AND #53
 NO 0535 TOTAL VOLTS 11.50 AMPS 22.4 OHMS .513 DATE 12/2/95 NAME JOHN L. MOSS

REMARKS (ADDED FOR CONSTRUCTION LOG) Driller Reported WATER AT 220'.
 Installed H/2' of 1" PE VENT PIPE, WITH THE BOTTOM 280'
 Perforated. COKE Breeze TO 115'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE	"		ANODE	"		ANODE	"		ANODE	"		ANODE	"
100	1.3		295	.6		490			685					
105	1.6		300	.5		495			690					
110	1.4		305	.9	8	500			695					
115	1.1		310	1.2		505			700					
120	1.1		315	1.2	7	510								
125	1.3		320	1.3		515								
130	1.1		325	1.7	6	520								
135	1.2		330	1.2		525								
140	1.8	15	335	1.1	5	530								
145	2.1		340	1.0		535								
150	2.2	14	345	1.0	4	540								
155	1.8		350	1.0		545								
160	1.2	13	355	1.0	3	550								
165	.7		360	1.2		555								
170	.3		365	1.4	2	560								
175	.4		370	1.0		565								
180	1.2	12	375	1.0	1	570								
185	1.0		380	.9		575								
190	.7		385	.6		580								
195	.6		390	.5		585								
200	.7		395	.6		590								
205	.5		400	.5		595								
210	.5		405	.5		600								
215	.5		410	T.D.	H/2'	605								
220	.6		415			610								
225	1.2		420			615								
230	1.1	11	425			620								
235	1.1		430			625								
240	1.4	10	435			630								
245	1.5		440			635								
250	1.1	9	445			640								
255	.7		450			645								
260	.6		455			650								
265	.6		460			655								
270	.7		465			660								
275	.5		470			665								
280	.5		475			670								
285	.5		480			675								
290	.4		485			680								

DISTRIBUTION - ORIGINAL - CORRECTION CPS FILE
 COPY - Division Correction Supervisor