

#239E = 30-039-25549

#67 = 30-039-06189

FEB 9 1997

#151 = 30-039-20271

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc. Location: Unit F Sec. 01 Twp 25 Rng 06

Name of Well/Wells. or Pipeline Serviced _____

CANYON Largo UNIT #239E, #67 AND #151Elevation _____ Completion Date 2/14/96 Total Depth 485' Land Type FCasing Strings, Sizes, Types & Depths 2 1/3 SET. 99' OF 8" PVC CASING.NO GAS, WATER, or Boulders were encountered During CASING.If Casing Strings are cemented, show amounts & types used CementedWITH 2H SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 300'.Depths gas encountered: NONEGround bed depth with type & amount of coke breeze used: 485' Depth.Used 128 SACKS OF Asbury 218R (6400#)Depths anodes placed: 390', 335', 292', 284', 276', 264', 256', 248', 240', 232', 224', 198', 190', 182', + 140'Depths vent pipes placed: SURFACE TO 485'.Vent pipe perforations: BOTTOM 370'.

Remarks: _____

RECEIVED
FEB 19 1997OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

WPS# 2888-W P/L NAME(S), NUMBER(S) CANYON LAIGO UNITS #239E, #67, AND #151
 -O -1491 TOTAL VOLTS 11.31 AMPS 22.9 - OHMS .494 DATE 7/14/96 NAME JOHN L. MOSS
 1492
 REMARKS (NOTES FOR CONSTRUCTION LOG)

Driller Reported Water AT 300'.
 Installed 485' of 1" PE Vent Pipe, WITH THE BOTTOM 370'
 Perforated. Cone Breeze To 115'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE			ANODE			ANODE			ANODE			ANODE	
100			295	.7		490			685					
105			300	.6		495			690					
110			305	.5		500			695					
115			310	.4		505			700					
120			315	.2		510								
125			320	.2		515								
130	1.5		325	.3		520								
135	2.1		330	.2		525								
140	1.9	-15	335	1.2	2	530								
145	1.3		340	.8		535								
150	.8		345	.7		540								
155	.5		350	.7		545								
160	.4		355	.8		550								
165	.4		360	.9		555								
170	.6		365	.5		560								
175	.5		370	.3		565								
180	1.0	14	375	.5		570								
185	2.2		380	.4		575								
190	2.3	13	385	.4		580								
195	2.4		390	1.3	1	585								
200	1.0	12	395	.6		590								
205	.5		400	.3		595								
210	.3		405	.3		600								
215	.5		410	.3		605								
220	1.9		415	.3		610								
225	2.1	11	420	.3		615								
230	2.1	10	425	.2		620								
235	2.2		430	.2		625								
240	1.2	9	435	.2		630								
245	1.9		440	.2		635								
250	1.9	8	445	.3		640								
255	2.0	7	450	.2		645								
260	1.7		455	.3		650								
265	1.0	6	460	.3		655								
270	.8		465	.2		660								
275	1.9	5	470	.2		665								
280	1.9		475	.2		670								
285	1.9	4	480	.2		675								
290	1.6	3	485			680								

T.D. 485'