

#287M = 30-039-25550

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit E Sec. 03 Twp 25 Rng 06

Name of Well/Wells. or Pipeline Serviced _____

CANYON LAT90 UNIT #287M

Elevation _____ Completion Date 2/15/96 Total Depth 478' Land Type F

Casing Strings, Sizes, Types & Depths 2 1/3 Set 99' of 8" PVC Casing.

NO GAS, WATER, or Boulders were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 21 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 420'

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 478' Depth.

Used 60 SACKS of Ashbury 218R + 33 SACKS of Loresco SW (6300#)

Depths anodes placed: 440', 350', 342', 334', 274', 266', 258', 245', 237', 229', 221', 209', 201', 193', + 185'

Depths vent pipes placed: SURFACE TO 478'

Vent pipe perforations: BOTTOM 360'

Remarks: _____

RECEIVED
FEB 1 9 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPB# 2887-W P/L NAME(S): NUMBER(S): CANYON LA90 UNIT #287M
 NO -1493 TOTAL VOLTS 11.13 AMPS 18.3 OHMS .608 DATE 2/15/96 NAME JOHN L. MOSS
 REMARKS (NOTES FOR CONSTRUCTION LOG)

Driller Reported WATER AT 420'.
 Installed 478' of 1" PE Vent Pipe, WITH THE BOTTOM 360' PERFORATED. COKE BREEZE TO 115'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE		
	ANODE			ANODE			ANODE			ANODE			
100	.4		295	.1		490			685				
105	.3		300	.2		495			690				
110	.9		305	.3		500			695				
115	.7		310	.2		505			700				
120	.1		315	.5		510							
125	.9		320	.7		515							
130	.7		325	.8		520							
135	.3		330	.9		525							
140	.5		335	1.3	4	530							
145	.3		340	1.7	3	535							
150	.2		345	2.0		540							
155	.2		350	1.3	2	545							
160	.3		355	.4		550							
165	.4		360	.4		555							
170	.4		365	.8		560							
175	.6		370	.4		565							
180	.9		375	.2		570							
185	2.0	15	380	.4		575							
190	1.5		385	.3		580							
195	1.2	14	390	.3		585							
200	1.3		395	.2		590							
205	2.1	13	400	.2		595							
210	.9	12	405	.2		600							
215	.9		410	.2		605							
220	1.0	11	415	.1		610							
225	1.0		420	.1		615							
230	1.0	10	425	.2		620							
235	1.4	9	430	.3		625							
240	1.6		435	.5		630							
245	1.6	8	440	1.1	1	635							
250	.7		445	.9		640							
255	1.3		450	.9		645							
260	1.6	7	455	.4		650							
265	1.5	6	460	.4		655							
270	1.4		465	.3		660							
275	1.0	5	470	.5		665							
280	.5		475	7.7	478'	670							
285	.4		480			675							
290	.3		485			680							