

47A = 30-045-29.332

DATE:

5/24/96

3430

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc. Location: Unit D Sec. 04 Twp 31 Rng 09

Name of Well/Wells or Pipeline Serviced _____

S.J. 32-9 #47AElevation _____ Completion Date 5/24/96 Total Depth 500' Land Type PCasing Strings, Sizes, Types & Depths 5/23 Set 60' of 8" PVC Casing.NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.If Casing Strings are cemented, show amounts & types used CementedWITH 15 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 390'.Depths gas encountered: NONEGround bed depth with type & amount of coke breeze used: 500' Depth.Used 94 SACKS OF ASBURY 218R (H700#)Depths anodes placed: H85', H60', H35', H25', H15', H05', 395', 370', 360', 300', 290', 280', 270', 260', + 250'.Depths vent pipes placed: SURFACE TO 500'.Vent pipe perforations: BOTTOM 300'.

Remarks: _____

RECEIVED
FEB 19 1997OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

2972-W R/L NAME(S), NUMBER(S) S.J. 32-9 #47A
 - 1495 TOTAL VOLTS 11.54 AMPS 22.4 - OHMS .515 DATE 5/24/94 NAME JOHN L. MOSS
 1497

REMARKS (NOTES FOR CONSTRUCTION LOG) Driller Reported Damp Areas AT 110', 170', 250', 320', AND WATER AT 390'. INSTALLED 500' OF 1" PE VENT PIPE, WITH THE BOTTOM 300' PERFORATED. CORK BREEZE TO 230'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
100			295	1.2		490	1.2		685					
105			300	1.1	-10	495	1.3		690					
110			305	.7		500	7.72	500	695					
115			310	.4		505			700					
120			315	.2		510			ANODE	DEPTH	NO	FULLY		
125			320	.2		515			-		CODE	CON'D		
130	.2		325	.5		520			1	485	1.2	3.9		
135	.1		330	.5		525			2	460	1.0	3.1		
140	.1		335	.3		530			3	435	1.0	3.9		
145	.2		340	.2		535			4	425	1.1	4.6		
150	.1		345	.2		540			5	415	1.0	4.8		
155	.5		350	.5		545			6	405	1.2	5.3		
160	.7		355	.9		550			7	395	.9	11.5		
165	.6		360	1.0	-4	555			8	370	1.1	11.8		
170	.5		365	.9		560			9	360	1.2	11.7		
175	.6		370	1.0	-8	565			10	300	1.0	11.4		
180	.6		375	.9		570			11	290	1.1	5.1		
185	.5		380	.1		575			12	280	1.2	5.5		
190	.4		385	.2		580			13	270	1.2	6.0		
195	.5		390	.9		585			14	260	1.2	5.8		
200	.9		395	.9	-7	590			15	250	1.2	5.2		
205	.9		400	.5		595			16					
210	1.0		405	1.1	-6	600			17					
215	.9		410	1.1		605			18					
220	.4		415	1.0	-5	610			19					
225	.5		420	1.1		615			20					
230	.4		425	1.1	-4	620			21					
235	.3		430	1.1		625			22					
240	.4		435	1.0	-3	630			23					
245	.4		440	.8		635			24					
250	1.1	-15	445	.6		640			25					
255	1.1		450	.2		645			26					
260	1.1	-14	455	.2		650			27					
265	1.2		460	.7	-2	655			28					
270	.9	-12	465	.8		660			29					
275	1.2		470	.5		665			30					
280	1.4	-12	475	.1		670								
285	1.3		480	.1		675								
290	1.2	-11	485	1.1	1	680								