

#10-30-039-22151

4/26/96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit L Sec. 03 Twp 23 Rng 03

Name of Well/Wells or Pipeline Serviced _____

JICATILLA JV KD #10

Elevation 7238 Completion Date 4/26/96 Total Depth 392' Land Type I

Casing Strings, Sizes, Types & Depths 4/25 SET 59' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used CEMENTED
WITH 15 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT FRESH WATER AT 110'

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 392' DEPTH.
USED 96 SACKS OF ASBURY 218R (4800#)

Depths anodes placed: 360, 345, 335, 325, 315, 300, 290, 280, 270, 260, 250, 220, 210, 200, + 190'

Depths vent pipes placed: SURFACE TO 392'

Vent pipe perforations: BOTTOM 260'

RECEIVED
FEB 19 1997

Remarks: _____

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number:

CPS GROUND BED CONSTRUCTION WORKSHEET

294500 JICA/AN/AN JV/KD #10
 AN/AN TOTAL 31.4 363 H/26/90 JICA/AN/AN
 REMARKS: Driller Reported WATER AT 115
 LNSHAW 300 GALLONS PER MIN. WORK TIME 18.00 MIN
 SHAW REPORTED COKE BICEPS TO 115

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
100			295	4.1		490			685					
105			300	4.2	-6	495			690					
110			305	2.9		500			695					
115			310	2.9		505			700					
120			315	2.9	-5	510								
125			320	2.6		515								
130			325	2.6	-4	520								
135			330	2.9		525								
140			335	2.8		530								
145			340	2.4		535								
150			345	3.1	-2	540								
155			350	2.5		545								
160			355	2.4		550								
165			360	2.2	-1	555								
170			365	2.0		560								
175			370	2.7		565								
180			375	2.3		570								
185			380	2.5		575								
190		-15	385	2.6		580								
195			390	7.0	392	585								
200		-14	395			590								
205			400			595								
210		-13	405			600								
215			410			605								
220		-12	415			610								
225			420			615								
230			425			620								
235			430			625								
240			435			630								
245			440			635								
250		-11	445			640								
255			450			645								
260		-10	455			650								
265			460			655								
270		-9	465			660								
275			470			665								
280		-8	475			670								
285			480			675								
290		-7	485			680								