

#9= 30-039-22154

4/25/96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit K Sec. 10 Twp 23 Rng 03

Name of Well/Wells or Pipeline Serviced _____

JICAFILLA JV KD #9

Elevation 7238' Completion Date 4/25/96 Total Depth 371' Land Type I

Casing Strings, Sizes, Types & Depths 4/24 Set 60' of 8" PVC Casing.

No Gas, Water, or Boulders Were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 15 SACKS

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT FRESH WATER AT 130'

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 371' Depth.

Used 88 SACKS OF ASBURY 218R (HH00#)

Depths anodes placed: 355', 345', 325', 315', 285', 275', 265', 230', 220', 210', 195', 185', 175', 165', + 155'

Depths vent pipes placed: SURFACE TO 371'

Vent pipe perforations: BOTTOM 240'

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

JOB # 2944-W D/L NAME (S), NUMBER (S) JICAFILLA JV KD #9
 NO. 2N52 TOTAL VOLTS 11.25 AMPS 32.8 OHMS .343 DATE 11/25/96 NAME JOHN L. MOSS

REMARKS (ADD FOR CONSTRUCTION LOG) Driller Reported WATER AT 130'
INSTALLED 371' OF 1" PE VENT PIPE, WITH THE BOTTOM
240' PERFORATED. COKE BREEZE TO 115'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	OHMS		ANODE	OHMS		ANODE	OHMS		ANODE	OHMS	
100			295	2.5		490			685			
105			300	2.3		495			690			
110			305	1.6		500			695			
115			310	2.7		505			700			
120			315	3.3	4	510			ANODE	DEPTH	LOG	FULL
125			320	2.9		515					OHMS	CON.
130	2.4		325	2.7	8	520			1	355	3.3	6.4
135	3.1		330	1.9		525			2	345	3.6	6.5
140	2.0		335	1.8		530			3	325	2.8	5.2
145	1.9		340	1.9		535			4	315	3.6	5.9
150	2.1		345	3.7	2	540			5	285	3.8	6.9
155	3.2	15	350	4.1		545			6	275	4.3	8.1
160	4.0	1	355	3.3	1	550			7	265	3.9	7.8
165	4.3	14	360	3.3		555			8	230	3.0	6.2
170	4.3		365	3.4		560			9	220	4.2	7.9
175	4.2	13	370	7.0	371'	565			10	210	3.8	7.1
180	4.1		375			570			11	195	3.1	6.6
185	3.9	12	380			575			12	185	3.9	8.2
190	3.5	2	385			580			13	175	4.3	9.1
195	3.0	11	390			585			14	165	4.2	9.1
200	2.3		395			590			15	155	3.3	7.8
205	2.4		400			595			16			
210	3.8	10	405			600			17			
215	4.2		410			605			18			
220	4.2	9	415			610			19			
225	4.0		420			615			20			
230	3.0	8	425			620			21			
235	2.3		430			625			22			
240	2.2		435			630			23			
245	1.9		440			635			24			
250	2.0		445			640			25			
255	1.9		450			645			26			
260	2.9		455			650			27			
265	3.9	7	460			655			28			
270	4.0		465			660			29			
275	4.2	6	470			665			30			
280	4.2		475			670						
285	3.5	5	480			675						
290	3.3		485			680						