

#10 = 30-039-23719

DATE:

5/1/96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit M Sec. 35 Twp 24 Rng 04

Name of Well/Wells or Pipeline Served

Medio CANYON #10

Elevation _____ Completion Date 5/1/96 Total Depth 377' Land Type I

Casing Strings, Sizes, Types & Depths 4/30 Set 59' of 8" PVC Casing

NO GAS, WATER, or Boulders were Encountered During Casing

If Casing Strings are cemented, show amounts & types used Cemented

WITH 15 SACKS

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT FRESH WATER AT 110'

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 377' DEPTH

Used 90 SACKS of Asbury 218R (H500#)

Depths anodes placed: 360', 350', 340', 320', 310', 295', 285', 275', 255', 218', 210', 170', 162', 150', + 140'

Depths vent pipes placed: SURFACE TO 377'

Vent pipe perforations: BOTTOM 250'

RECEIVED
FEB 19 1997

Remarks:

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CP# 2952-W D/L NAME(S), NUMBER(S) Medio Canyon #10
 - 2F70 TOTAL VOLTS 11.92 AMPS 31.4 - CHMS 380 DATE 5/1/96 NAME JOHN L. MOSS

REMARKS (NOTE FOR CONSTRUCTION LOG) Driller Reported Water AT 110'.
 Installed 377' OF 1" PE VENT PIPE, WITH THE BOTTOM
 250' PERFORATED. COKE BREEZE TO 115'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE			ANODE			ANODE			ANODE	
100			295	2.6	6	490			685		
105			300	2.1		495			690		
110			305	2.2		500			695		
115			310	2.1	5	505			700		
120			315	3.9		510					
125			320	2.9	4	515					
130	4.1		325	2.1		520					
135	3.7		330	1.7		525			1	360	3.1
140	3.8	-15	335	1.8		530			2	350	3.2
145	3.8		340	2.4	3	535			3	340	2.5
150	2.6	-14	345	3.2		540			4	320	2.9
155	1.9		350	3.2	2	545			5	310	3.1
160	2.2	-13	355	2.8		550			6	295	2.6
165	3.3		360	3.0	1	555			7	285	3.8
170	2.4	-12	365	3.7		560			8	275	4.0
175	1.4		370	4.0		565			9	255	2.4
180	1.4		375	Y.D.	377'	570			10	218	2.0
185	.9		380			575			11	210	3.2
190	1.0		385			580			12	190	2.4
195	1.7		390			585			13	162	2.7
200	1.7		395			590			14	150	2.6
205	1.5		400			595			15	140	3.8
210	2.9	-11	405			600			16		
215	2.5		410			605			17		
220	2.0	10	415			610			18		
225	2.0		420			615			19		
230	2.0		425			620			20		
235	1.9		430			625			21		
240	1.8		435			630			22		
245	1.7		440			635			23		
250	1.9		445			640			24		
255	2.4	-9	450			645			25		
260	2.3		455			650			26		
265	1.9		460			655			27		
270	3.2		465			660			28		
275	4.0	-8	470			665			29		
280	4.1		475			670			30		
285	3.8	-7	480			675					
290	2.7		485			680					