

#12 = 30-039-25309

4/17/96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit J Sec. 18 Twp 26 Rng 03

Name of Well/Wells or Pipeline Serviced _____

JICA 111A 98 #12

Elevation 6970 Completion Date 4/17/96 Total Depth 491' Land Type I

Casing Strings, Sizes, Types & Depths 4 1/2" Set 80' of 8" PVC Casing.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented
WITH 22 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT FRESH WATER AT 115'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 491' DEPTH.
USED 130 SACKS OF ASBURY 218R (6500#)

Depths anodes placed: 470', 460', 400', 360', 350', 315', 290', 280', 265', 250', 235', 200', 190', 180', + 170'.

Depths vent pipes placed: SURFACE TO 491'.

Vent pipe perforations: BOTTOM 360'.

RECEIVED
FEB 1 9 1997

Remarks: _____

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

Land Type may be shown: F-Federal; I-Indian; S-State; P-Free.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

2951-W P/L NAME(S), NUMBER(S) JICARILLA 98 #12
 2019 TOTAL VOLTS 11.38 AMPS 29.4 OHMS .387 DATE 4/17/96 NAME JOHN L. MOSS

REMARKS (NOTES FOR CONSTRUCTION LOG) Drillet Reported Water AT 110'.
 INSTALLED 491' OF 1" PE VENT PIPE, WITH THE BOTTOM
 360' PERFORATED. CORE BREEZE TO 115'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	"		ANODE	"		ANODE	"		ANODE	"	
100			295	2.1		490	T.D	400	685			
105			300	1.0		495			690			
110			305	1.1		500			695			
115			310	.9		505			700			
120			315	2.2	-6	510						
125			320	2.2		515						
130			325	1.8		520						
135			330	.8		525						
140	1.8		335	.7		530						
145	1.4		340	1.8		535						
150	1.2		345	1.7		540						
155	1.3		350	2.3	-5	545						
160	1.0		355	2.4		550						
165	1.2		360	2.1	-4	555						
170	2.6	-15	365	1.5		560						
175	2.6		370	1.0		565						
180	2.8	-14	375	.8		570						
185	2.4		380	.7		575						
190	2.6	-13	385	.6		580						
195	2.9		390	1.1		585						
200	2.5	-12	395	2.1		590						
205	1.8		400	2.5	-3	595						
210	1.4		405	2.0		600						
215	.9		410	1.8		605						
220	1.0		415	1.5		610						
225	2.3	-11	420	.5		615						
230	1.9		425	.6		620						
235	1.0		430	.5		625						
240	1.3		435	.4		630						
245	1.1		440	.5		635						
250	2.5	-10	445	.7		640						
255	2.0		450	.5		645						
260	2.5		455	1.8		650						
265	2.4	-9	460	2.3	2	655						
270	1.8		465	2.2		660						
275	1.5		470	2.3	1	665						
280	2.7	-8	475	2.2		670						
285	1.0		480	2.0		675						
290	2.6	-7	485	1.0		680						