

3399

#2E = 30-045-27269

#3E = 30-045-25023

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil/Inc. Location: Unit C Sec. 34 Twp 30 Rng 13

Name of Well/Wells. or Pipeline Serviced _____

McCord #2E AND #3EElevation 5681 Completion Date 1/17/95 Total Depth 444' Land Type PCasing Strings, Sizes, Types & Depths 1 1/2 SET 97' OF 8" PVC CASING.NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.If Casing Strings are cemented, show amounts & types used CEMENTEDWITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONEDepths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. HIT FRESH WATER AT 150'. A WATER SAMPLE WAS TAKEN.Depths gas encountered: NONEGround bed depth with type & amount of coke breeze used: 444' DEPTH.USED 56 SACKS OF LORESCO SWDepths anodes placed: 415', 405', 395', 385', 375', 365', 355', 345', 335', 325', 310', 295', 280', 265', + 200'Depths vent pipes placed: SURFACE TO 444'.Vent pipe perforations: BOTTOM 310'.

Remarks: _____

RECEIVED
FEB 19 1997OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 6163-W P/L NAME(S), NUMBER(S) McCord *2E And *3E
 NO. W901 TOTAL VOLTS 12.74 AMPS 37.8 - OHMS .337 DATE 11/17/95 NAME John L. Mo
W902

REMARKS (NEEDS FOR CONSTRUCTION LOG) Driller Reported WATER @ 150'.
WATER SAMPLE WAS TAKEN. ALSO HIT 10'(170'-180') OF GRAVEL. INSTALLED AAA
OF 1" PE VENT PIPE, WITH THE BOTTOM 310' PERFORATED. COKE
Breeze To 115'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE			ANODE			ANODE			ANODE		
100			295	2.3	12	490			685			
105	.4		300	2.1		495			690			
110	.3		305	2.3		500			695			
115	.3		310	2.4	11	505			700			
120	.3		315	2.1		510			ANODE	DEPTH	NO	FULLY
125	.3		320	2.3		515					COKE	COKE
130	.3		325	2.3	10	520			1	415'	2.1	6.1
135	.3		330	2.2		525			2	405'	2.3	6.6
140	.2		335	2.5	9	530			3	395'	2.3	6.0
145	.2		340	2.5		535			4	385'	2.4	6.8
150	.9		345	2.4	8	540			5	375'	2.2	5.9
155	.4		350	2.4		545			6	365'	2.3	6.7
160	.7		355	2.2	7	550			7	355'	2.5	7.7
165	.13		360	2.1		555			8	345'	2.3	7.9
170	2.1		365	2.3	6	560			9	335'	2.5	8.1
175	1.7		370	2.0		565			10	325'	2.4	8.0
180	1.7		375	2.1	5	570			11	310'	2.4	8.2
185	1.5		380	2.4		575			12	295'	2.6	8.0
190	2.1		385	2.3	4	580			13	280'	2.4	7.8
195	2.3		390	2.0		585			14	255'	2.4	7.7
200	2.4	15	395	2.2	3	590			15	200'	2.6	9.8
205	2.1		400	2.0		595			16			
210	2.0		405	2.2	2	600			17			
215	1.5		410	2.0		605			18			
220	1.5		415	2.1	1	610			19			
225	1.7		420	2.0		615			20			
230	2.0		425	1.8		620			21			
235	2.1		430	1.7		625			22			
240	2.3		435	2.0		630			23			
245	2.1		440	2.2		635			24			
250	2.1		445	T.D. AAA		640			25			
255	2.4	14	450			645			26			
260	2.3		455			650			27			
265	2.3		460			655			28			
270	2.0		465			660			29			
275	2.1		470			665			30			
280	2.4	13	475			670						
285	2.2		480			675						
290	2.4		485			680						

DISTRIBUTION - ORIGINAL - DEPARTMENT CPS FILE

CCBY - Division Correction Supervisor

CCBY - Region Correction Specialist