Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No.

NMSE08996

SUNDRY NOTICES AND REPORTS ON WELLS

SUBMIT IN TRIPLICATE -	Other instructions	s on reverse side	ningion, NM. in	Unit or CA/Agreement, Name and/or N	
1. Type of Well Oil Well X Gas Well Other 2. Name of Operator ConocoPhillips Company		TO ON THE PERSON OF THE PERSON	8. W	NMNM78423A 8. Well Name and No. SJ 32-7 Unit #232A	
a. Address 5525 Highway 64, NBU 3004, Farmingt Location of Well (Footage, Sec., T., R., M., or Survey L Unit C (NENW), 1170' FNL & 1330' FWI Section 8, T32N, R7W	Description)	3b. Phore No. (include are 505-599-3454	30 - 0. 10. F Basiu 11. C	PI Well No. 45-31738 ield and Pool, or Exploratory Area 1 Fruitland Coal Younty or Parish, State Juan, NM	
12. CHECK APPROPRIATE	BOX(ES) TO IN	DICATE NATURE OF N	IOTICE, REPORT, (OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injecti	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Start/Re Reclamation Recomplete Temporarily Abando Water Disposal	Well Integrity Other	
Describe Proposed or Completed Operation (clearly If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. It testing has been completed. Final Abandonment Nettermined that the final site is ready for final inspect 8/29/03 RIH w/8-3/4" bit & tagged RIH w/7", 20#, J-55 casing and set 10 bbls. Pumped 465 sx (1214 cf & 0.2% Antifoam. Tail - 100 sx (2% CaCl2, 0.25#/sx Cellophane & 0 Bumped plug w/1300 psi. Circ. 40 cuf off casing. Installed trash report.	lete horizontally, give soformed or provide the fite operation results i lotices shall be filed or tion.) cement @ 215'. t @ 3205'. RU - 216.2 bbl slu 128 cf - 22.8 b .2% Antifoam. bbls good ceme	ubsurface locations and meas Bond No. on file with BLM/ n a multiple completion or re ally after all requirements, inc Drilled cement an Schlumberger to cem rry) Class G cement bl slurry) 50/50 Cl Released wiper plug nt to surface. RD	ured and true vertical dep BIA. Required subseque completion in a new interluding reclamation, have d then formation ent. Pumped 30 w/3% Extender, ass G POZ w/2% G and displaced p Schlumberger. N	oths of all pertinent markers and zones. In reports shall be filed within 30 days val, a Form 3160-4 shall be filed once been completed, and the operator has to 3205'. Circ hole. bbls FW w/dye in last 0.25#/sx Cellephane, el, 5#/sx Gilsonite, lug w/128 bbls FW. D BOP. Set slips and	

9/2/03 THIS SPACE FOR FEDERAL OR STATE OFFICE USE Approved by Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.