Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

·····	\/	 1	9	-1	Ŀ	2./	LC	as	C	S	CI	ıa	ŀ
		/		١.				_	_	_	_	_	

SUNDRY NOTICES	NMSF078998							
Do not use this form for abandoned well. Use For	A. If Indian, Allottee or Tribe Name							
SUBMIT IN TRIPLICATE -					CA/Agreement, Nam	ne and/or l		
1. Type of Well Oil Well X Gas Well Other		10 10 21 22 7		8. Well Name	and No.	<del></del>		
2. Name of Operator		SEP CO.	- PA	C1 22 7 Um	.i+ #000A			
ConocoPhillips Company		p= 2003	3	SJ 32-7 Un 9. API Well N				
3a. Address	07.104	3b. Phone No. (include ar	ea code)	30-045-317	58			
5525 Highway 64, NBU 3004, Farmingt. 4. Location of Well (Footage, Sec., T., R., M., or Survey 1		505-599-3454	<b>∀. ∀.</b>	10. Field and I	Pool, or Exploratory	/ Area		
Unit F (SENW), 1655' FNL 7 1795' FW				Basin Frui	tland Coal			
Section 9, T31N, R7W	-			11. County or Parish, State				
		<u> </u>		San Juan,	NM			
12. CHECK APPROPRIATE	BOX(ES) TO IN	DICATE NATURE OF I	NOTICE, REP	ORT, OR OTH	HER DATA			
TYPE OF SUBMISSION		TY	PE OF ACTION					
<u></u>								
Notice of Intent	Acidize	Deepen	Production	(Start/Resume)	Water Shut-Off	î		
X Subsequent Report	Alter Casing	Fracture Treat	Reclamatio	n	Well Integrity			
X Sansoquent Report	Casing Repair	New Construction	Recomplet	e	X Other			
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporaril	y Abandon	7" casing re	port		
	Convert to Inject	ion Plug Back	Water Disp	osal				
testing has been completed. Final Abandonment Netermined that the final site is ready for final inspect 9/7/03 RIH w/8-3/4" bit & tagged hole. RIH w/7", 20#, J-55 casing bbls FW w/dye in last 10 bbls. Pt 0.25#/sx Cello-flake. Tail - 100 CaCl2, 0.25#/sx Cello-flake, 5#/s. Bumped plug w/1300 psi @ 0151 hrs cut off casing. RD & released rie	cement @ 210'. and set @ 3168 umped Lead - 45 sx (126 cf - 2 x Gilsonite, 0. 9/10/03. Circ	Drilled out cement C. RU Schlumberger O sx (1175 cf - 209 22.43 bbl slurry) Cl 2% Antifoam. Dropp c. 40 bbls good ceme	t and then f r to cement. 9.26 bbl slu lass G 50/50 ped plug and ent to surfa	ormation to Pumped a rry) Class POZ, 2% Be displace w ce. ND BOF	o 3168'. Circ preflush of 3 G, 3% Econol entonite, 2% w/126 bbls wa	c. 30 ite, ter.		
14. I hereby certify that the foregoing is true and correct		Title						
Name (Printed/Typed)	Patsy Clugstor	n SHEAR	Administrati	ve Assista	nt			
Take link		Date 9/15/	'03			· <del>-</del>		
THIS	SPACE FOR FEI	DERAL OR STATE OF	FICE USE	ACCEPTED	FOR RECORL			
Approved by		Title		Da		l		
Conditions of approval, if any, are attached. Approval of	f this notice does not v	varrant or Office		SEH 1	<del>-8 2003</del>			
certify that the applicant holds legal or equitable title to	those rights in the sub	ject lease		ERDAMAK!	n na saithe a tha a <b>th thinne</b> an an			