

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2007 JUN 13 AM 11:14

1. Type of Well
GAS

2. Name of Operator
CDX RIO, LLC

3. Address & Phone No. of Operator

2010 Afton Place, Farmington, New Mexico 87401 (505) 326-3003

4. Location of Well, Footage, Sec., T, R, M
1550'FSL, 1590'FEL, Sec.19, T-26-N, R-5-W, NMPM

RECEIVED
BLM
210 FARMINGTON, NM

5. Lease Number
Jicarilla Contract 110
6. If Indian, All. or
Tribe Name
Jicarilla Apache
7. Unit Agreement Name

8. Well Name & Number

Jicarilla A #3E
9. API Well No.

30-039-22582
10. Field and Pool

Basin Dakota
11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment ☐ Change of Plans
☒ Subsequent Report	☐ Recompletion ☐ New Construction
☐ Final Abandonment	☐ Plugging ☐ Non-Routine Fracturing
	☒ Casing Repair ☐ Water Shut off
	☐ Altering Casing ☐ Conversion to Injection
	☐ Other

RCVD JUN28'07
OIL CONS. DIV.
DIST. 3

13. Describe Proposed or Completed Operations

5-11-07 MIRU. SD for weekend.
5-14-07 Blow well & CO. ND WH. NU BOP. Test BOP, OK. TIH, tag up @ 7581'. Work tbg loose. SDON.
5-15-07 TOO H w/2 3/8" tbg & 4 1/2" pkr. TIH w/4 1/2" csg scrapper to 7528'. TOO H. TIH w/4 1/2" BP & pkr, set BP @ 7287', set pkr @ 7245'. Load hole, establish circ w/82 bbl 2% KCl wtr. PT BP to 1400 psi, OK. Made multiple tool settings. Isolate hole in csg @ 5108-5125'. PT csg to 1000 psi @ 0-5108', OK. PT csg below pkr @ 5125-7287', OK. TIH to 7150'. Dump 10' sd on top of BP. TOO H. SDON.
5-16-07 (Verbal approval to squeeze from Steve Mason, BLM; notify Bryce Hammond w/Jicarilla Tribe). TOO H w/pkr. TIH w/4 1/2" FB pkr, set @ 4792'. Load csg w/wtr. Establish injection into csg leak w/2 bbl min @ 700 psi. Plug #1: pump 94 sx Type III cmt outside csg; pump 6 sx Type III cmt inside csg to 5011'. Displace 1 bbl below pkr. Pressure up to 1500 psi/15 min. TOC inside csg @ 5011'. Shut in w/1500 psi. WOC. SDON.
5-17-07 WOC. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Oltmanns Title Agent Date 5-17-07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date ACCEPTED FOR RECORD

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD 6/28

JUN 26 2007
FARMINGTON FIELD OFFICE
S

5-18-07 Release pkr, TOO. TIH w/3 7/8" drill bit to 4967'. Establish circ. Drill out stringers @ 4967-5006'. Drill cmt @ 5006-5120'. Circ hole clean. PT csg to 1000 psi/15 min, OK. TOO. w/bit. SD for weekend.

5-21-07 TIH w/4 1/2" csg scraper to 5438'. TOO. to 4798'. PT csg to 1000 psi/10 min, OK. TOO. w/csg scraper. TIH w/retrieving tool to 7255'. Blow well & CO. SDON.

5-22-07 Blow well & CO to BP @ 7284'. Pump 10 bbl 2% KCl down csg. Latch on to BP, TOO. SDON.

5-23-07 TIH, blow well & CO to 7580'. SDON.

5-24-07 Blow well & CO. Tag up @ 7584'. TOO. TIH w/232 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 7410'. (SN @ 7409'). ND BOP. NU WH. RD. Rig released.